



Frigomax Series 71" Refrigerated Display Case with Straight Glass, 21 cu. ft., 1 Year Warranty

(Model: FRSC71B)

★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Warranty



SPECIAL FEATURES

- Large Display Volume**
 The 21.4 cu ft interior gives a busy bakery or cafe counter room to display a wide variety of pastries and chilled goods between restocks.
- Consistent Cold-Holding**
 A temperature range of 32 to 41 degrees Fahrenheit keeps chilled baked goods and desserts within food-safe holding temperatures throughout service hours.
- Clear Visibility**
 Straight-glass doors and glass shelving allow customers and staff to view merchandise from the front without opening the cabinet, reducing cold air loss on a commercial floor.
- Low-GWP Refrigerant**
 R-290 refrigerant is a hydrocarbon option with a lower global warming potential, aligning with energy and environmental considerations in modern commercial kitchens.
- Recognized Certifications**
 ETL Listed, ETL Sanitation Listed, and DOE 2017 Compliant certifications confirm the unit meets established safety, sanitation, and energy efficiency standards for restaurant and foodservice use.
- Simple Installation**
 The plug-in, freestanding design requires no hardwiring or built-in cabinetry, letting a chef or restaurant owner place and relocate the unit with minimal setup time.



PRODUCT OVERVIEW

The Frigomax Series 70.9" Dry and Refrigerated Bakery Display Case is a freestanding, straight-glass refrigerated showcase suited for bakeries, cafes, patisseries, and commercial kitchen retail counters that need to present baked goods at food-safe temperatures.

The cabinet holds 21.4 cubic feet of product and maintains a temperature range of 32 to 41 degrees Fahrenheit, making it appropriate for displaying pastries, cakes, and chilled desserts that require consistent cold-holding. Glass shelving throughout the interior keeps merchandise visible from multiple angles, and LED lighting highlights displayed items without generating excessive heat inside the cabinet.

The straight-glass door configuration gives staff and customers a clear, unobstructed view of the full display from the front, while the stainless steel exterior is straightforward to clean in a busy commercial kitchen environment. The unit runs on 110V at 60Hz and draws 7.49 amperes, so it is compatible with standard commercial electrical circuits. The plug-in installation type means no hardwiring is required. Dimensions are 33.5" (L) x 70.9" (W) x 48.4" (H).

The display case uses R-290 refrigerant, a low-GWP hydrocarbon option recognized in environmentally aware commercial kitchen operations. It carries ETL Listed, ETL Sanitation Listed, and DOE 2017 Compliant certifications, confirming it meets established safety, sanitation, and energy standards. A 1-year warranty is included with purchase.

CERTIFICATIONS

ETL Listed

ETL Sanitation Listed

DOE 2017 Compliant

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Type	Refrigerated Display Case	Display Case Type	Straight Glass
Material	Stainless Steel	Capacity	21.4
Door Type	Glass	Voltage	110
Hertz	60	Installation Type	Freestanding
Country of Origin	China	Selling Unit	1/Each
Refrigerant Type	R-290	Amps	7.49
Shelf Material	Glass	Temperature Range	32°F to 41°F
Product Width	70.9	Product Depth	33.5
Product Height	48.4	Lighting	LED
Series	Frigomax Series		