



FrostLine Series 27" Reach-In Refrigerator, 1 Door, 23 cu.ft., Stainless Steel, 1 Year Compressor Warranty
(Model: FLRR27)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Compressor

SPECIAL FEATURES

- ✓ **Efficient Performance**
Certified energy-efficient operation with R-290 hydrocarbon refrigerant and ECM fans, reducing operational costs while maintaining optimal cooling performance.

✓ **Commercial-Grade Durability**
Full stainless steel construction inside and out ensures long-lasting performance and easy cleaning in demanding commercial environments.

✓ **Enhanced Security**
Keyed door lock and magnetic door gasket ensure contents remain secure and maintain airtight seal.

✓ **Efficient Cooling**
Forced-air refrigeration system with 1/5 HP bottom-mounted compressor ensures consistent temperature throughout.

✓ **Quality Assured**
cETLus, Energy Star, and ETL Sanitation certifications plus 1-year compressor warranty guarantee reliable performance and safety standards.
- ✓ **Precise Temperature Control**
Dixell electronic thermostat with digital LED display maintains consistent temperature between 33°F-41°F for reliable food storage.

✓ **Spacious Storage**
23 cubic feet capacity with four adjustable PE-coated wire shelves provides flexible storage options.

✓ **Easy Mobility**
Four 4-inch swivel casters with brakes allow convenient repositioning while maintaining stability when locked.

✓ **Bright Lighting**
Shielded LED lighting with rocker switch control provides clear visibility of stored items.



PRODUCT OVERVIEW

The FrostLine Series Reach-In Refrigerator is a durable and efficient refrigeration unit designed for commercial kitchens. Made with a stainless steel exterior and interior, this silver-colored unit ensures long-lasting performance and hygiene. Its single solid swing door provides secure access to a spacious 23 cubic feet capacity, supported by four adjustable PE-coated wire shelves (21.5" x 24.3") for flexible storage.

The unit includes a keyed door lock for added security. A vacuum release air pressure relief door allows for smooth door operation. It operates on a forced-air refrigeration system with ECM fans powered by a 1/5 HP bottom-mounted compressor using R-290 hydrocarbon refrigerant (3 oz capacity). It features a temperature range of 33°F to 41°F, controlled by a precise Dixell electronic thermostat with a digital LED display for easy monitoring.

The unit also includes auto defrost functionality and shielded LED lighting with rocker switch control. Electrical specifications include 115 V voltage, 3 A current, 1-phase, 60 Hz frequency, and a 9-foot power cord with a NEMA 5-15P plug. Measuring 26.8" W x 32.7" D x 82.3" (with casters), this freestanding refrigerator is equipped with four 4-inch swivel casters with brakes for easy mobility and stability.

The door hinges on the right and features a magnetic door gasket to ensure an airtight seal. The foamed-in-place polyurethane insulation, copper-coated condenser, and copper evaporator help maintain optimal cooling and energy efficiency. Certified by cETLus, ETL Sanitation, and Energy Star, the unit offers a 1-year compressor warranty.

CERTIFICATIONS



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	1 Door	Access Type	Door
Amps	3 ampere	Capacity	23 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors	Material	Stainless Steel
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	9 foot
Refrigerant Type	R-290	Sections	1 Section
Shelf Material	PE Coated Wire Shelves	Temperature Range	33°F to 41°F
Type	Reach-In Refrigerator	Voltage	115 volt



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Hertz	60 hertz	Hinge Location	Right
Horsepower	1/5 horsepower	Installation Type	Freestanding
Country of Origin	China	Selling Unit	1/Each
Door Gasket	Magnetic Door Gasket	Lock Type	Keyed Door Lock
Number of Casters	4 Casters	Refrigeration Type	Forced Air
Caster Type	Swivel with brake	Interior Material	Stainless Steel
Temperature Control	Dixell Electronic Thermostat	Refrigerant Class	Hydrocarbon
Insulation Material	Foamed-in-Place Polyurethane	Caster Size	4 inch
Height with Casters	82.3 inch	Shelf Size	21.5 x 24.3 in
Product Weight	276 pound	Product Width	27 inch
Product Depth	33 inch	Product Height	82 inch
Shipping Depth	34.5 inch	Shipping Height	84.7 inch
Shipping Weight	313 pound	Shipping Width	29.9 inch
Refrigerant Capacity	3.0 oz	Condenser Coating	Copper
Evaporator	Copper	Lighting	LED, Shielded, Rocker Switch Control
Cooling Fans	ECM Fan	Defrost Type	Auto Defrost
Temperature Display	Digital LED Display	BTU/HR - Refrigerator	1670
Air Pressure Relief Door	Vacuum Release	Interior Depth	27.5 inch
Interior Height	59.4 inch	Interior Width	22 inch
Series	FrostLine Series		