COFFEE BREWING SYSTEMS

CBS-2250 NG Brewers

1.5 GALLON BREWING SYSTEM

Shown with **D449 6.0L / 1.5G LUXUS® Thermal Dispenser**






CAPACITIVE TOUCHSCREEN DISPLAY

The NG line features a capacitive LED touchscreen display. Set brew times, program recipe buttons and more with just the touch of a finger. It's as easy as a smartphone.



LED STATUS BAR

Quickly identify where your machine is at in the brewing process from anywhere in the room. The LED Status Bar changes color during the brewing process to let you know when it's ready to brew, brewing, almost done and ready to serve.



BREW BASKET LOCKS

Brew baskets lock in place during the brewing process for added safety and quality control.

FETCO®

DISPENSERS

CBS-2250 NG Brewers

DISPENSERS

D449

6.0 Liter / 1.5 Gallon LUXUS® Thermal Dispenser
L4D-15

NSF



D480

6.0 Liter / 1.5 Gallon LUXUS® Sight Gauge Dispenser
LGD-15

NSF



D009

6.0 Liter / 1.5 Gallon LUXUS® Portable Thermal Dispenser
TPD-15

NSF



All dispensers **SOLD SEPARATELY**.

D450

8.0 Liter / 2.0 Gallon LUXUS® Thermal Dispenser
L4D-20

NSF

FOR USE WITH CBS-1253 PLUS BREWER



D481

8.0 Liter / 2.0 Gallon LUXUS® Sight Gauge Dispenser
LGD-20

NSF

FOR USE WITH CBS-1253 PLUS BREWER







BREW BASKET DESIGN

Advanced brew basket design provides a deeper bed depth and superior thermal insulation for better extraction.



CASCADING SPRAY DOME

Patented design provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.



ECO MODE

Reduces tank temperature during periods of non-operation to cut down on electricity usage.

ACCESSORIES

CBS-2250 NG Brewers

NOTE

Coffee brewers are available with **Plastic** or **Metal** brew basket options. Material type is of personal preference and does not affect flavor profile, however if you are looking for color identification the plastic brew baskets are the best option.

BREW BASKETS AND PAPER FILTERS

Item Number	Brew Basket	Coffee Capacity	Filter Size	Filter SKU	Filter/Case
All configurations	Standard **Plastic** / Stainless Steel	Up to 12oz / 340g	15" x 5.5"	F001	500/cs

B001280B1

16" x 6"
Stainless Steel
Brew Basket



B015280BN2BK

16" x 6"
Plastic Brew
Basket



F001

15" x 5.5"
Paper Filters



Contact Customer Service or your Sales Person for more options.

COLORED BREW BASKET HANDLE INSERTS

1023.00180.00
Blue Insert



1023.00190.00
Red Insert



1023.00191.00
Green Insert



1023.00192.00
Orange Insert



WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A039	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water
Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) / 1ea. 3/8" x 4' connection hose / 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve

BWT BESTMAX

In-Line Water
Filtration System



SET INCLUDES: 1ea. filter cartridge / 1ea. universal filter head / 1ea. wall mounting bracket Braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences

TECHNICAL SPECIFICATIONS

NORTH AMERICA

CBS-2251 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2251US-1B230-MA110	16x6" Metal	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	15.0 / 56.9	
E2251US-1B230-PA110	16x6" **Plastic**	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	15.0 / 56.9	

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	5.89 / 22.30

CBS-2252 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2252US-UB230-MA110 DUAL PHASE	16x6" Metal	208-240 208-240	2 x 3.0 kW / 240 V 3 x 3.0 kW / 240 V	1 3	2+G 3+G	4.6-6.1 6.9-9.1	No Cord No Cord	22.1-25.4 19.2-22.1	15.9 / 60.4 23.9 / 90.6	
E2252US-UB230-PA110 DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 3.0 kW / 240 V 3 x 3.0 kW / 240 V	1 3	2+G 3+G	4.6-6.1 6.9-9.1	No Cord No Cord	22.1-25.4 19.2-22.1	15.9 / 60.4 23.9 / 90.6	
E2252US-UB250-MA110 DUAL PHASE	16x6" Metal	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	
E2252US-UB250-PA110 DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	10.48 / 39.67

CBS-2253 NG 2.0 Gallon Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2253US-UB230-MA110 DUAL PHASE	16x6" Metal	208-240 208-240	2 x 3.0 kW / 240 V 3 x 3.0 kW / 240 V	1 3	2+G 3+G	4.6-6.1 6.9-9.1	No Cord No Cord	22.1-25.4 19.2-22.1	15.9 / 60.4 23.9 / 90.6	
E2253US-UB230-PA110 DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 3.0 kW / 240 V 3 x 3.0 kW / 240 V	1 3	2+G 3+G	4.6-6.1 6.9-9.1	No Cord No Cord	22.1-25.4 19.2-22.1	15.9 / 60.4 23.9 / 90.6	
E2253US-UB250-MA110 DUAL PHASE	16x6" Metal	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	
E2253US-UB250-PA110 DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	10.48 / 39.67

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.

TECHNICAL SPECIFICATIONS

INTERNATIONAL

CBS-2251 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2251IN-1B140-PA110	16x6" **Plastic**	200-240	1 x 4.0 kW / 240 V	1	L/N/PE	2.9-4.1	No Cord	14.3-17.1	10.6 / 40.3	NSF cULus
E2251IN-1B150-PA110	16x6" **Plastic**	200-240	1 x 5.0 kW / 240 V	1	L/N/PE	3.6-5.1	No Cord	17.8-21.2	13.3 / 50.4	NSF cULus
E2251IN-1B230-PA110[1]	16x6" **Plastic**	200-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.3-6.1	No Cord	21.2-25.4	15.0 / 56.9	NSF cULus
E2251NM-1B230-PA110	16x6" **Plastic**	208-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.6-6.1	No Cord	22.2-25.4	15.0 / 56.9	NSF NOM
E2251CE-1C230-PA110	16x6" **Plastic**	230/400	2 x 3.0 kW / 240 V	1	2L/N/PE	5.6	No Cord	12.4	14.9 / 56.4	NSF CE

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	5.89 / 22.30

CBS-2252 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2252IN-3C330-PA110[1]	16x6" **Plastic**	220/380-240/415	3 x 3.0 kW / 240 V	3	3L/N/PE	7.7-9.1	No Cord	11.9-12.9	23.9 / 90.6	NSF cULus
E2252IN-3C350-PA110[1]	16x6" **Plastic**	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	30.0 / 133.7	NSF cULus
E2252IN-1B230-PA110[1]	16x6" **Plastic**	200-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.3-6.1	No Cord	21.2-25.4	15.9 / 60.4	NSF cULus
E2252IN-1B250-PA110	16x6" **Plastic**	200-240	2 x 5.0 kW / 240 V	1	L/N/PE	7.0-10.1	No Cord	35.1-42.1	26.6 / 100.7	NSF cULus
E2252IN-3C340-PA110	16x6" **Plastic**	220/380-240/415	3 x 4.0 kW / 240 V	3	3L/N/PE	10.2-12.1	No Cord	15.7-17.1	30.0 / 113.7	NSF cULus
E2252NM-1B250-PA110	16x6" **Plastic**	208-240	2 x 5.0 kW / 240 V	1	2+G	7.6-10.1	No Cord	36.5-42.1	26.6 / 100.7	NSF NOM
E2252NM-UB250-PA110[1] DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	NSF NOM
E2252CE-3C330-PA110	16x6" **Plastic**	230/400	3 x 3.0 kW / 240 V	3	3L/N/PE	8.4	No Cord	12.3	22.1 / 83.6	NSF CE
E2252CE-3C350-PA110	16x6" **Plastic**	230/400	3 x 5.0 kW / 240 V	3	3L/N/PE	13.9	No Cord	20.3	30.0 / 113.7	NSF CE

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	10.48 / 39.67

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.

TECHNICAL SPECIFICATIONS

INTERNATIONAL

CBS-2253 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2253IN-3B330-PA110[1]	16x6" **Plastic**	220/380-240/415	3 x 3.0 kW / 240 V	3	3L/N/PE	7.7-9.1	No Cord	11.9-12.9	23.9 / 90.6	NSF cULus
E2253IN-3B350-PA110[1]	16x6" **Plastic**	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	30.0 / 133.7	NSF cULus
E2253IN-1B230-PA110[1]	16x6" **Plastic**	200-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.3-6.1	No Cord	21.2-25.4	15.9 / 60.4	NSF cULus
E2253IN-1B250-PA110	16x6" **Plastic**	200-240	2 x 5.0 kW / 240 V	1	L/N/PE	7.0-10.1	No Cord	35.1-42.1	26.6 / 100.7	NSF cULus
E2253IN-3B340-PA110	16x6" **Plastic**	220/380-240/415	3 x 4.0 kW / 240 V	3	3L/N/PE	10.2-12.1	No Cord	15.7-17.1	30.0 / 113.7	NSF cULus
E2253NM-1B250-PA110	16x6" **Plastic**	208-240	2 x 5.0 kW / 240 V	1	2+G	7.6-10.1	No Cord	36.5-42.1	26.6 / 100.7	NSF NOM
E2253NM-UB250-PA110[1] DUAL PHASE	16x6" **Plastic**	208-240 208-240	2 x 5.0 kW / 240 V 3 x 5.0 kW / 240 V	1 3	2+G 3+G	7.6-10.1 11.4-15.1	No Cord	36.5-42.1 31.7-36.5	26.6 / 100.7 30.0 / 113.7	NSF NOM
E2253CE-3B330-PA110	16x6" **Plastic**	230/400	3 x 3.0 kW / 240 V	3	3L/N/PE	8.4	No Cord	12.3	22.1 / 83.6	NSF CE
E2253CE-3B350-PA110	16x6" **Plastic**	230/400	3 x 5.0 kW / 240 V	3	3L/N/PE	13.9	No Cord	20.3	30.0 / 113.7	NSF CE

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	10.48 / 39.67

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.

DIMENSIONS

CBS-2251 NG Brewer


DIMENSIONS	Height (A)	Width (B)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	36.88" 93.67 cm	12.75" 32.38 cm	22.5" 57.15 cm	17.13" 43.51 cm	22.5" 57.15 cm	12.13” 30.80 cm
Shipping Dimensions	37.0" 93.98 cm	18.0" 45.72 cm	24.0" 60.96 cm	N/A	N/A	N/A

WEIGHT	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	53 lbs 24.0 kg	106 lbs 48.1 kg
Shipping Weight	63 lbs 28.5 kg	N/A

CBS-2252 NG Brewer

DIMENSIONS	Height (A)	Width (C)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	36.88" 93.67 cm	21.88" 55.57 cm	22.5" 57.15 cm	17.13" 43.51 cm	22.5" 57.15 cm	12.13” 30.80 cm
Shipping Dimensions	37.0" 93.98 cm	24.0" 60.96 cm	27.0" 68.58 cm	N/A	N/A	N/A

WEIGHT	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	77 lbs 34.9 kg	174 lbs 78.8 kg
Shipping Weight	97 lbs 44.0 kg	N/A



FETCO®

WEBSITE
fetco.com

EMAIL
inquiries@fetco.com

PHONE
+1.847.719.3000
1.800.338.2699

FAX
+1.847.719.3001

ADDRESS
FETCO®
600 Rose Road
Lake Zurich, IL 60047, USA

© Copyright 2024 FETCO® is a mark of Food Equipment Technologies Company.
Dispensers, airpots, paper filters, water filters, stands, accessories and options sold separately

Rev. 1.0 2024.08.30 Digital Letter