



ProKitchen Series 72" Straight Glass Refrigerated Bakery Display Case, Stainless Steel, 110-120V

(Model: PKDRBDC72-3)

★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 1 Year
Compressor: 5 Years



SPECIAL FEATURES

- Wide Display Capacity**
 28.6 cb3 capacity supports chilled bakery and dessert display in commercial cafés and bakeries.
- Adjustable Shelving**
 Three adjustable glass shelves support flexible product arrangement in bakery display applications.
- Temperature Control**
 Digital temperature control supports operation between 32°F and 53.6°F for refrigerated food display.
- Sliding Door Access**
 Two sliding doors support easy access in high-traffic bakery and retail environments.
- LED Visibility**
 LED interior lighting supports clear visibility of displayed bakery and dessert items.
- Certified Refrigeration**
 cETLus Listed, ETL Sanitation Listed, and NSF/CSA compliant for commercial bakery display use. It includes a 1-year parts and labor warranty and a 5-year compressor warranty.



PRODUCT OVERVIEW

The ProKitchen Series Refrigerated Bakery Display Case is designed for commercial bakeries, cafés, restaurants, and retail food service environments requiring chilled display and storage of bakery items. It features stainless steel and glass construction with a silver finish and a 28.6 cb3 capacity. The straight glass design supports product visibility with a freestanding installation type. Its dimensions are 72.5" (L) x 27.1" (W) x 55.5" (H).

The ProKitchen refrigerated display case operates on 110–120 V, 1 phase, 60 Hz electrical supply with 440 W power and 4.9 amps. It uses a NEMA 5-15P plug type and supports R-290 refrigerant with a ventilated cooling system. The bottom-mounted compressor supports stable refrigeration performance in commercial bakery and food retail environments.

This bakery display case operates within a temperature range of 32°F to 53.6°F with digital temperature control and display. It includes automatic defrost functionality and LED interior lighting for visibility of displayed products. The double tempered glass structure supports clear product presentation in commercial bakery service applications.

The unit includes two sliding doors, three adjustable glass shelves, and shelf sizing optimized for bakery display use. It features 4 casters, including 2 with brakes, for mobility and positioning in commercial food service layouts. The system is cETLus Listed, ETL Sanitation Listed, and conforms to NSF/CSA standards. It includes a 1-year parts and labor warranty and a 5-year compressor warranty.

CERTIFICATIONS

cETLus Listed

ETL Sanitation Listed

Conforms to NSF/CSA Standard

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Type	Refrigerated Bakery Display Case	Display Case Type	Straight Glass
Material	Stainless Steel and Glass	Capacity	28.6 cubic feet
Number of Shelves	3 Shelves	Plug Type	NEMA 5-15P
Power Cord Length	72 inch	Number of Doors	2 Doors
Door Type	Sliding	Voltage	110-120 volt
Hertz	60 hertz	Phase	1 Phase
Color	Silver	Installation Type	Freestanding
Country of Origin	China	Selling Unit	1/Each
Compressor Location	Bottom Mounted	Refrigerant Type	R-290
Amps	4.9 ampere	Shelf Material	Glass



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Temperature Range	32°F to 53.6°F	Temperature Control	Digital
Shelf Size	Bottom & Middle: 67.12" L x 14.57" D / Top: 67.12" L x 12.20" D	Product Weight	540 pound
Product Depth	27.1 inch	Product Height	55.5 inch
Product length	72.5 inch	Shipping Depth	30 inch
Shipping Height	60 inch	Shipping Length	75.1 inch
Shipping Weight	640 pound	Lighting	LED Interior Light
Defrost Type	Automatic	Interior Depth	22.83 inch
Interior Height	33.07 inch	Series	ProKitchen Series
Glass Type	Double Tempered Glass	Shelf Type	Adjustable
Casters	With Casters	Number of Casters	4 Casters (2 with Brakes, 2 without Breaks)
Power Type	Electric	Wattage	440 watt
Display	Digital	Cooling Type	Ventilated
Interior Length	69.1 in		

ProKitchen Series 72" Straight Glass Refrigerated Bakery Display Case, Stainless Steel, 110-120V

Model: PKDRBDC72-3



SALES & SUPPORT
(866) 446-7322

Chat on WhatsApp

CONNECT WITH US

