



PolarBox Series 6' x 6' Quick Ship Walk-In Freezer With Floor & Top Mounted Refrigeration

(Model: PBFWF6X6-TM)



★★★★★ (4.7/5)

[Buy Now](#)

WARRANTY

10-Year Panel, 1-Year Door Parts, 2-Year Compressor & Parts, 1-Year Labor on Refrigeration Unit

SPECIAL FEATURES

- ✓ **Durable Construction**
24-gauge white galvanized steel with floor provides long-lasting strength.
- ✓ **Secure Access**
Solid swing door with keyed lock, self-closing design, heating wire, and pressure relief vent.
- ✓ **Eco-Friendly Design**
CFC and HFC-free materials provides environmentally safe operation.
- ✓ **Stable Power**
Operates on 208/230 V, 60 Hz, single-phase hardwired connection.
- ✓ **Comprehensive Warranty**
10-year panel, 1-year door parts, 2-year compressor and parts, and 1-year labor coverage.
- ✓ **Reliable Insulation**
4-inch polyurethane with R-28 thermal resistance maintains stable freezing temperatures.
- ✓ **Easy Setup**
Modular cam-lock and tongue & groove hinge design allow precise alignment and simple installation.
- ✓ **Consistent Cooling**
Top-mounted compressor and self-contained refrigeration unit maintain steady temperatures.
- ✓ **Certified Safety**
UL Listed, NSF Listed, and DOE compliant for commercial refrigeration standards.



PRODUCT OVERVIEW

The PolarBox Series Walk-In Freezer is ideal for cafes and commercial kitchens, offering reliable storage for perishable goods. Made in America, it is constructed with white galvanized steel panels of 24-gauge thickness, providing strength and long-term durability. The floor giving stable support for heavy loads. The overall dimensions are 6 ft (W) x 6 ft (D) x 7 ft (H), providing ample interior space for commercial refrigeration.

The unit features a solid swing door with a height of 77 inches and has a keyed lock for secure access. It also features a modular cam-lock with a tongue & groove hinge design for precise alignment. The self-closing, flush-mounted door includes a heating wire and pressure relief vent to maintain consistent internal temperatures. The freezer has a top-mounted compressor for optimal cooling efficiency.

This commercial walk-in freezer has 4-inch polyurethane insulation with R-28 thermal resistance to retain cold and operate efficiently. The materials are CFC & HFC free, supporting environmentally responsible construction. The unit is hardwired, runs on 208/230 V, 60 Hz single-phase power, and uses R-448A refrigerant for optimal cooling performance.

This walk-in freezer is UL listed in the US, NSF listed, and DOE certified for safety and sanitation. Warranty coverage includes 10 years on panels, 1 year on door parts, 2 years on the compressor and parts, and 1 year on labor on the refrigeration unit, giving full manufacturer support. The unit includes a condensing unit and evaporator for balanced cooling performance.

CERTIFICATIONS

UL Listed US

NSF Listed

DOE

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Product Width	79 inch	Product Depth	79 inch
Product Height	91 inch	Hertz	60 hertz
Phase	1 Phase	Voltage	208/230 volt
Door Type	Solid	Door Style	Swing
Insulation Thickness	4 inch	Insulation Material	Polyurethane
Door Lock	Keyed Lock	Material	White Galvanized Steel
Plug Type	Hardwired	Refrigerant Type	R-448A
Usage	Indoor/Outdoor	Type	Walk-In Freezer
Country of Origin	Proudly Made in America	Selling Unit	1/Each
Nominal Depth	6 ft	Nominal Width	6 foot



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Door Height	77 inch	Floor	With Floor
Included	Condensing Unit and Evaporator	Gauge	24 Gauge
Thermal Resistance	R-28	Features	Self-Closing, Flush-Mounted Door, Heating Wire and Pressure Relief Vent
Number of Doors	1 Door	Nominal Height	7 foot
Compressor Location	Top Mounted	Hinge Type	Modular Cam-Lock, Tongue & Groove Design
Material Type	CFC & HFC Free	Refrigeration Type	Top Mounted Refrigeration
Series	PolarBox Series	Floor Material	Standard Galvanized Steel Floor

PolarBox Series 6' x 6' Quick Ship Walk-In Freezer With Floor & Top Mounted Refrigeration

Model: PBFWF6X6-TM



SALES & SUPPORT
 (866) 446-7322


[Chat on WhatsApp](#)

CONNECT WITH US



