



ChillCore Series 59" Open Air Refrigerated Display Case, 14.3 Cu.ft, 2 Shelves (Model: CDODRS59)

★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Parts & Labor



SPECIAL FEATURES

- Ventilated Cooling**
 Ventilated cooling operates within the 35.6°F to 50°F temperature range for food display in commercial kitchen environments.
- Two-Side Glass**
 Double tempered glass at two sides supports visibility of items from multiple angles in display areas.
- Mobile Stability**
 Four casters with two brakes and two adjustable feet support positioning within commercial kitchen layouts.
- Digital Temperature Control**
 A digital temperature controller with display supports monitoring during restaurant food handling operations.
- LED Lighting Setup**
 LED lighting at the top and under shelf supports illumination inside the refrigerated showcase.
- Certified Unit**
 cETLus Listed, ETL Sanitation Listed, and NSF Certified, with a 1-year warranty by the manufacturer.



PRODUCT OVERVIEW

The ChillCore Series Refrigerated Display Case is a freestanding open air / refrigerated unit designed for commercial kitchens, bakeries, cafés, and food retail environments. It operates on 115 V, 1 phase, 60 Hz with a 12.9 A electrical load and uses ventilated cooling for consistent air circulation across the display chamber.

The body is constructed using powder coated steel and glass in a black finish with double tempered glass at two sides. It features a curved design measuring 59" (W) x 33.2" (D) x 45.9" (H), suitable for commercial floor-based food display installations. The interior uses mirror stainless steel 304 for structured product placement and durability.

Temperature is maintained between 35.6°F and 50°F through a digital temperature controller with display. The system includes automatic defrost and automatic condensate evaporation, supporting continuous refrigerated operation in food service environments.

This unit includes LED lighting positioned at the top and under the shelf for display visibility. It is supported by 4 casters with 2 brakes and 2 adjustable feet for movement, positioning, and leveling. The display case is cETLus Listed, ETL Sanitation Listed, and NSF Certified and includes a 1-year warranty by the manufacturer.

CERTIFICATIONS

cETLus Listed

ETL Sanitation Listed

NSF Certified

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Amps	12.9 ampere	Capacity	14.3 cubic feet
Casters	With Casters	Color	Black
Number of Shelves	2 Shelves	Phase	1 Phase
Temperature Range	35.6°F to 50°F	Type	Horizontal Air Curtain Merchandiser
Voltage	115 volt	Hertz	60 hertz
Installation Type	Freestanding	Interior Material	Mirror Stainless Steel 304
Country of Origin	China	Material	Powder Coated Steel
Selling Unit	1/Each	Product Weight	379.1 pound
Product Width	59 inch	Product Depth	33.2 inch
Product Height	45.9 inch	Shipping Depth	36.2 inch



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Shipping Height	50.9 inch	Shipping Weight	462.9 pound
Shipping Width	62 inch	Features	Automatic Condensate Evaporation
Series	ChillCore Series	Lighting	LED Lighting (Top, Under Shelf)
Number of Casters	4 Casters with 2 Brakes	Temperature Control	Digital Temperature Controller with Display
Glass Type	Double Tempered Glass at 2 Sides	Defrost Type	Automatic Defrost
Cooling Type	Ventilated Cooling	Shelf Type	1 Stainless Steel Shelf with 2 Steps
Included	Front Curtain	Feet Type	2 Adjustable Feet
Compressor Location	Bottom Mounted	Display Case Type	Open Air / Refrigerated
Shape	Curved		

ChillCore Series 59" Open Air Refrigerated Display Case, 14.3 Cu.ft, 2 Shelves

Model: CDODRS59



SALES & SUPPORT
 (866) 446-7322


[Chat on WhatsApp](#)

CONNECT WITH US
[f](#)
[y](#)
[in](#)
[ig](#)