



CoolEdge Series 47" Merchandiser Refrigerator, 2 Swing Glass Doors

(Model: CEMR47WB)



★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 1 Year
Compressor: 1 Year

SPECIAL FEATURES

- Defined Temperature Range**
 The listed 33°F to 40°F range supports refrigerated food handling in commercial kitchens and restaurants.
- Fan Assisted Cooling**
 Fan assisted cooling with a copper evaporator and condenser supports internal air circulation across section.
- Certified Equipment**
 cETLus Listed, ETL Sanitation Listed, and NSF Listed certifications align with commercial food service standards.
- Digital Control System**
 Digital control with LED display supports temperature adjustment and monitoring during food service operations.
- Adjustable Shelving**
 Ten adjustable shelves support organized storage and food handling tasks in commercial kitchens.
- Warranty Coverage**
 It includes a 1-year parts and labor and a 1-year compressor warranty by the manufacturer.



PRODUCT OVERVIEW

The CoolEdge Series merchandiser refrigerator is designed for commercial kitchen refrigeration and front-of-house display in restaurants, cafés, and food service operations. This freestanding unit features a two-section configuration with two swing-style glass doors, supporting refrigerated storage with clear product visibility. The black and white coated steel exterior aligns with routine cleaning and daily use in commercial kitchen environments.

This merchandiser refrigerator operates within a temperature range of 33°F to 40°F using digital temperature control. Fan assisted cooling works with a copper evaporator and fan-assisted condenser to support internal airflow. A bottom-mounted compressor rated at 1/2 HP operates with R290 refrigerant, aligning with standard commercial refrigeration system requirements.

Interior organization includes ten adjustable shelves arranged across two sections, supporting structured food handling for chefs and service staff. LED interior lighting supports visibility during service hours, while an LED display works with digital controls for clear temperature monitoring. A replaceable door gasket supports routine maintenance in commercial kitchen operations.

Overall dimensions are 31.87" (L) x 47.25" (W) x 80.37" (H), supporting placement along service or display walls. Mobility is supported by four 5" casters for repositioning during cleaning or layout changes. Electrical requirements include 110 V, 60 Hz, single-phase power, a NEMA 5-15P plug, and a 9 ft power cord. It includes a 1-year warranty by the manufacturer.

CERTIFICATIONS

- cETLus Listed
- ETL Sanitation Listed
- NSF Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	2 Doors	Access Type	Doors
Amps	20 ampere	Casters	With Casters
Color	Black	Compressor Location	Bottom Mounted
Door Type	Glass	Number of Shelves	10 Shelves
Phase	1 Phase	Plug Type	NEMA 5-15P
Power Cord Length	9 foot	Refrigerant Type	R-290
Sections	2 Sections	Temperature Range	33°F to 40°F
Type	Merchandiser Refrigerator	Voltage	110 volt
Wattage	690 watt	Hertz	60 hertz
Hinge Location	Left / Right	Horsepower	1/2 horsepower



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Installation Type	Freestanding	Country of Origin	China
Material	Coated Steel	Selling Unit	1/Each
Lighting	LED Lighting	Defrost Type	Automatic
Number of Casters	4 Casters	Series	CoolEdge Series
Door Style	Swing	Product Weight	363 pound
Product Width	47.25 inch	Product Depth	31.87 inch
Product Height	80.37 inch	Shipping Depth	32.5 inch
Shipping Height	82.37 inch	Shipping Weight	396 pound
Shipping Width	49.25 inch	Evaporator	Copper Evaporator
Temperature Control	Digital Control	Shelf Type	Adjustable
Control Type	Digital	Display	LED Display
Caster Size	5 inch	Condenser Type	Fan-Assisted Condenser
Cooling Type	Fan Assisted Cooling	Door Gasket	Replaceable

CoolEdge Series 47" Merchandiser Refrigerator, 2 Swing Glass Doors

Model: CEMR47WB



SALES & SUPPORT
 (866) 446-7322

 Chat on WhatsApp

CONNECT WITH US



