VALYR™
BY STRATA GPO

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

VF3(LES/NES) / VF4(LES/NES) / VF5(LES/NES) ENERGY STAR® Commercial Fryers - Liquid Propane (L) / Natural Gas (N)

MODEL: ☐ VF3(LES/NES) ☐ VF4(LES/NES) ☐ VF5(LES/NES)



VF3 / VF4




VF5

SPECIAL FEATURES


- ENERGY STAR® Certified
- Stainless steel fry tank, 35/45/65 lb. capacities
- 1 1/4" full port ball type drain valve
- Stainless steel door with magnet to secure closed door
- High-grade galvanized non-corrosive finish sides and back
- Twin fry baskets with plastic coated handles
- Behind the door snap action millivc thermostat control - (adjusts from 200° to 400° with standing pilot)
- High temperature limit control to shut off gas supply to the main burners and pilot
- High temperature limit control to shut off gas supply to the main burners and pilot

TECHNICAL DATA


MODEL	EXTERNAL DIMENSIONS	WORKING HEIGHT	TANK SIZE	BTU / HR	FRY COMPARTMENT CAPACITY
VF3(LES/NES)	15 1/2" x 30" x 48 9/10" (394 x 762 x 1242 mm)	34 4/5" (884 mm)	14" x 14"	65,000 BTU	35 lbs.
VF4(LES/NES)	15 1/2" x 30" x 48 9/10" (394 x 762 x 1242 mm)	34 4/5" (884 mm)	14" x 14"	84,000 BTU	45 lbs.
VF5(LES/NES)	21" x 30" x 48 9/10" (533 x 762 x 1242 mm)	34 4/5" (884 mm)	20" x 21"	105,000 BTU	65 lbs.




FRONT




SIDE



FRONT




SIDE



TOP

VF3 / VF4



TOP

VF5

Intertek Intertek

Available in export voltages and plug types.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

© 2026 VALYR