



FrostLine Series 27" Reach-In Freezer, 1 Door, 23 cu.ft., Stainless Steel, 1 Year Compressor Warranty
(Model: FLRF27)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Compressor

SPECIAL FEATURES

- ✓ **High Storage Capacity**
Spacious 23 cu. ft. interior with four PE-coated wire shelves, each supporting 100 lbs for optimal commercial frozen goods storage.

✓ **Premium Construction Quality**
Durable stainless steel interior and exterior with foamed-in-place polyurethane insulation ensures optimal temperature retention and longevity.

✓ **Temperature Retention**
Right-hinged door equipped with keyed lock, vacuum release, and magnetic gasket ensures secure and tight seal.

✓ **Easy Mobility**
Four 4-inch swivel casters with brakes provide convenient mobility and stable positioning in commercial kitchens.

✓ **Professional Certification**
cETLus, ETL Sanitation, and Energy Star certifications ensure compliance with commercial foodservice standards.
- ✓ **Efficient Cooling**
Eco-friendly R-290 refrigerant and efficient 1/2 HP compressor with ECM cooling fans deliver 2000 BTU/hr of sustainable cooling performance.

✓ **Precise Temperature Control**
Dixell electronic thermostat with digital LED display maintains consistent -10°F temperature with auto defrost functionality.

✓ **Superior Cooling System**
Copper evaporator and copper-coated condenser maximize thermal transfer efficiency for reliable performance.

✓ **Convenient Access**
Wide door opening facilitates effortless loading and unloading of commercial frozen goods.

✓ **Reliable Warranty**
Comprehensive 1-year compressor warranty provides peace of mind for commercial kitchen operators.



PRODUCT OVERVIEW

The FrostLine Series Reach-In Freezer is a high-performance commercial kitchen freezer designed for use in hotels, restaurants, and catering facilities. Built with a durable stainless steel interior and exterior in a sleek silver finish, this one-section, solid-door freezer offers a generous 23 cu. ft. storage capacity. Four PE-coated wire shelves (21.5" x 24.3"), each with a 100 lb. load capacity, provide organized storage for frozen goods.

The swing door is right-hinged, features a vacuum release, has a magnetic gasket for a tight seal, and is equipped with a keyed lock for security. Powered by a bottom-mounted 1/2 HP compressor with ECM cooling fans, this freezer delivers 2000 BTU/hr of efficient forced-air cooling using eco-friendly R-290 hydrocarbon refrigerant (3.88 oz capacity). A copper evaporator and copper-coated condenser enhance thermal transfer and durability.

The Dixell electronic thermostat with digital LED display maintains a consistent temperature of -10°F. Auto defrost ensures hassle-free maintenance, while LED interior lighting with shielded rocker switch control enhances visibility. Measuring 26.8" W × 32.7" D × 82.3" H with casters, this freestanding unit is easy to move and stabilize using four 4-inch swivel casters with brakes. The 57.6" door opening width allows easy loading and unloading.

The freezer connects via a 9 ft power cord and NEMA 5-15P plug to a 115 V, 8 A, single-phase, 60 Hz power supply. Foamed-in-place polyurethane insulation ensures optimal cold retention. Certified by cETLus, ETL Sanitation, and Energy Star, this reach-in freezer meets rigorous commercial foodservice standards. It is backed by a 1-year compressor warranty.

CERTIFICATIONS



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	1 Door	Access Type	Door
Amps	8 ampere	Capacity	23 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Solid
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	9 foot
Refrigerant Capacity	3.88 oz	Refrigerant Type	R-290
Sections	1 Section	Type	Reach-in Freezer
Voltage	115 volt	Hertz	60 hertz
Hinge Location	Right	Horsepower	1/2 horsepower



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Installation Type	Freestanding	Interior Material	Stainless Steel
Material	Stainless Steel	Selling Unit	1/Each
Shelf Material	PE Coated Wire Shelves	Lighting	LED, Shielded, Rocker Switch Control
Door Gasket	Magnetic Door Gasket	Refrigerant Class	Hydrocarbon
Refrigeration Type	Forced Air Cooling	Defrost Type	Auto Defrost
Temperature Control	Dixell Electronic Thermostat	Insulation Material	Foamed-in-Place Polyurethane
Caster Size	4 inch	Interior Depth	27.5 inch
Interior Height	59.4 inch	Interior Width	22 inch
Height with Casters	82.3 inch	Door Opening Width	57.6 inch
Shelf Size	21.5 x 24.3 in	Product Weight	289 pound
Product Width	27 inch	Product Depth	33 inch
Product Height	82 inch	Shipping Depth	34.5 inch
Shipping Height	84.7 inch	Shipping Weight	328 pound
Shipping Width	29.9 inch	Country of Origin	China
Lock Type	Keyed Door Lock	Undershelf Capacity	100 Lbs per Shelf
Caster Type	Swivel with brake	Number of Casters	4 Casters
Condenser Coating	Copper	Evaporator	Copper
Air Pressure Relief Door	Vacuum Release	Cooling Fans	ECM Fan
Temperature Display	Digital LED Display	BTU/HR - Freezer	2000 british thermal unit
Door Style	Swing	Series	FrostLine Series
Temperature	-10° fahrenheit		