



ESPRESSO GRINDER

E65W GbS



E65W GbS



The E65W Grind-by-Sync (GbS) elevates the E65S Grind-by-Weight to the next level of intelligence. It is the first espresso grinder featuring the groundbreaking technology of The Sync System which seamlessly adjusts the grinder with the parameters received from the coffee machine. By combining cloud technology and smart algorithms, the technology guarantees the most consistent and repeatable quality coffee moments along all stores and shifts around the world.

The E65W Grind-by-Sync allows for direct control by the barista or, when synchronized with a coffee machine, for automatic alignment according to your target extraction time to generate the perfect shot. This means it can function as a standalone grinder or as a synced grinder.

For even more precision, Mahlkönig's well-established Disc Distance Detection (DDD) capability is enriched by an electrical motor which adjusts the gap between burrs, unlocking repeatable and precise results.

Along with the Grind-by-Sync technology, the grinder is bolstered by the intuitive Mahlkönig Sync mobile app and desktop interface. This allows you to easily setup and synchronize devices, whilst also getting valuable and in-depth data insights to monitor and manage decision-making process remotely and locally in all your stores.

Take the next step in grinding and enter the world of unmatched speed and consistency - with the E65W Grind-by-Sync.

TECHNICAL DETAILS

Voltage // frequencies // phases // nominal power 220-240 V // 50/60 Hz // 1~ // 440 W  
110-127 V // 60 Hz // 1~ // 580 W  
100 V // 50/60 Hz // 1~ // 550/700 W

Idle speed 1400 rpm (50 Hz)  
1700 rpm (60 Hz)

Burr diameter 65 mm

Burr material Special steel

Average grinding capacity\* 4-5 g/s @250um  
5-6 g/s @250um

Burr grind life (median setting): 800 kg

Bean hopper capacity 1200 g

Dimensions (w x h x d) 19.5 x 62 x 28.3 cm

Dimensions of packing (w x h x d) 69.7 x 28.7 x 47.5 cm

Net weight 12.2 kg

Gross weight 14 kg

Certifications CE, CB, ETL Safety, ETL Sanitation

Standards Conforms to  
IEC/EN 60335-1  
IEC/EN 60335-2-64  
Certified to  
UL 763  
CSA C22.2 No. 195  
NSF/ANSI 8

Standard colors (Other colors on request) Polished aluminum, matte black  
Polished aluminum, matte black & white

OPTIONAL ACCESSORIES

Bean hopper approx. 250 g  
Bean hopper approx. 1800 g  
Burr replacement tool  
Calibration weight 1 kg  
CB-certified aluminum adapter for Cans

KEY FEATURES

- Grind-by-Sync cloud technology enabling intelligent synchronization between grinder and coffee machine for repeatable and consistent coffee quality
- Mahlkönig Sync mobile app for easy setup of grind-brew-synchronization and monitoring of selected grind-brew events
- Mahlkönig Sync desktop app giving valuable in-depth data insights to monitor and manage decision-making processes remotely and locally
- High-precision and micrometric adjustment of the gap between burrs with an electric motor
- Grind-by-Weight technology featuring a high-precision load cell for real-time dosing control during grinding process
- Patented Disc Distance Detection (DDD) enabling accurate settings of the degree of fineness
- Time savings and quality assurance through integrated Portafilter Detection
- 65 mm diameter special steel burrs
- Active cooling system maintaining low grinding temperatures
- Adjustable illuminated spout providing a clean and centered coffee outlet
- Pleasantly quiet grinding
- High-resolution 88.3 mm display with a wide viewing angle

