



IceVault Series 60” Back Bar Cooler, 2 Solid Doors, 1 Year Warranty
(Model: IVBBS59)

★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 1 Year

Compressor: 1 Year



SPECIAL FEATURES

- ✓ **Large Storage Volume**

17 cu ft capacity supports high beverage throughput in a primary back bar refrigerator.
- ✓ **Consistent Cooling**

33°F to 40°F range maintains reliable temperature performance in a back bar fridge during service hours.
- ✓ **Efficient Refrigerant**

R-290 refrigerant supports stable, efficient cooling performance for beverage storage.
- ✓ **Sturdy Swing Doors**

Two solid swing doors support fast access in high-volume environments.
- ✓ **Warranty Coverage**

Comes with 1-year parts & labor and 1-year compressor warranty.
- ✓ **Durable Construction**

Stainless steel interior walls, floor, and ceiling support heavy daily use in bar coolers commercial operations.
- ✓ **Secure Access**

Keyed lock provides controlled entry during peak shifts behind the bar.
- ✓ **Adjustable Storage**

Four heavy-duty PVC-coated shelves accommodate cans, bottles, and specialty beverage formats inside the back bar refrigerator.
- ✓ **Commercial Certification**

ETL Sanitation Listed and cETLus align with foodservice requirements.



PRODUCT OVERVIEW

The IceVault Series IVBBS59 Primary Back Bar Refrigerator is built for bars, restaurants, clubs, and lounges that need reliable beverage storage with a 17 cu ft capacity. It fits cleanly under standard bar counters as a back bar fridge and can be paired with a secondary glass door back bar cooler to create a two-unit setup for high-volume service and product display in bar coolers commercial environments.

A vinyl-coated black exterior, stainless steel countertop, and stainless steel interior support long-term durability. LED lighting improves visibility during service, while the 60" (W) × 28" (D) × 36" (H) footprint integrates smoothly into most under-bar layouts requiring a primary back bar refrigerator.

Powered by 115 V, 60 Hz, 1-phase, the unit uses R-290 refrigerant with a 3.5 A draw and 3/7 HP compressor. Electronic controls manage a 33°F–40°F holding range suitable for keeping bottled and canned beverages at serving temperature. Two solid swing doors with a keyed lock support controlled access in busy back bar operations.

The unit carries ETL Sanitation Listed and cETLus certifications for commercial foodservice use. Warranty coverage includes 1-year parts & labor and 1-year compressor support.

CERTIFICATIONS

ETL Sanitation Listed

cETLus

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	2 Doors	Access Type	Doors
Amps	3.5 ampere	Capacity	17 cubic feet
Countertop Type	Stainless Steel	Door Type	Solid
Features	Heavy duty Shelves	Material	Vinyl Coated Steel
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Refrigerant Type	R-290
Temperature Range	33°F to 40°F	Voltage	115 volt
Hertz	60 hertz	Hinge Location	Left / Right
Horsepower	3/7 horsepower	Exterior Finish	Vinyl Coated Black Finish
Country of Origin	China	Color	Black & Silver



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Selling Unit	1/Each	Installation Type	Freestanding
Product Weight	253 pound	Product Width	60 inch
Product Depth	28 inch	Product Height	36 inch
Shipping Depth	30.5 inch	Shipping Height	42.1 inch
Shipping Weight	298 pound	Shipping Width	61.2 inch
Type	Back Bar Refrigerator	Series	IceVault Series
Shelf Material	PVC Coated	Defrost Type	Auto Defrost
Lighting	LED lighting	Lock Type	Keyed Lock
Shelf Type	Adjustable	Control Type	Electronic
Interior Material	Stainless Steel		

IceVault Series 60" Back Bar Cooler, 2 Solid Doors, 1 Year Warranty

Model: IVBS59



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

