



Platinum Frost Series 72" Commercial Reach In Freezer, 54 Cu.ft, 3 Door, Stainless Steel, -8°F to 0°F

(Model: PFRF72)

★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 2 Years
Compressor: 6 Years



SPECIAL FEATURES

- ✓ **Massive Storage Capacity**

54 cubic feet of storage space with nine epoxy-coated wire shelves across three sections, perfect for large-scale commercial kitchen operations.
- ✓ **Premium Construction Quality**

Durable stainless steel interior and exterior construction with silver finish, designed for long-lasting commercial use.
- ✓ **Extended Warranty Protection**

Comprehensive 2-year parts and labor warranty, plus extended 6-year compressor warranty for long-term reliability assurance.
- ✓ **Easy Mobility**

Mounted on casters for simple repositioning, supporting flexible kitchen layouts and cleaning access.
- ✓ **Simple Power Requirements**

Operates on standard 115V power with 2.3 amp draw, including 5.9-foot cord and NEMA 5-15P plug for easy installation.
- ✓ **Temperature Control Precision**

Electronic temperature control maintains consistent temperatures between -8°F to 0°F, with auto defrost functionality for reliable operation.
- ✓ **Enhanced Access Design**

Three solid swing doors with left/right hinges and bright LED lighting provide easy visibility and convenient access to stored items.
- ✓ **Eco-Friendly Cooling**

Uses R-290 hydrocarbon refrigerant with top-mounted, self-contained compressor system for environmentally conscious operation.
- ✓ **Safety Certified**

ETL Listed and ETL Sanitation Listed certifications ensure compliance with safety and hygiene standards.



PRODUCT OVERVIEW

This reach-in freezer is a freestanding, high-capacity unit built for commercial kitchens that need reliable frozen storage. Made of stainless steel with a silver finish, it offers 54 cubic feet of space across 3 sections, with 3 solid doors and 9 epoxy-coated steel wire shelves for organized storage. The stainless steel interior measures 68.1" W x 23.2" D x 57.1" H and is illuminated with LED lighting.

It operates on a 115V, 60 Hz, 1 Phase connection, drawing 2.3 amps, and includes a 5.9 ft power cord with a NEMA 5-15P plug. The top-mounted, self-contained refrigeration system uses R-290 hydrocarbon refrigerant and maintains a temperature range of -8°F to 0°F. Electronic controls and auto defrost ensure consistent performance, while the precision ventilated refrigeration system provides even cooling.

Hinges on both the left and right allow easy access, and heavy-duty casters support smooth mobility. Exterior dimensions are 72" W x 31.5" D x 77.9" H. Certified ETL and ETL Sanitation Listed, the unit includes a 2-year parts and labor warranty and a 6-year compressor warranty.

CERTIFICATIONS

- ETL Listed
- ETL Sanitation Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Power Cord Length	5.9 foot	Amps	2.3 ampere
Hertz	60 hertz	Phase	1 Phase
Voltage	115 volt	Plug Type	NEMA 5-15P
Refrigerant Type	R-290	Temperature Range	-8°F to 0°F
Number of Doors	3 Doors	Access Type	Doors
Casters	With Casters	Color	Silver
Compressor Location	Top Mounted	Door Type	Solid
Features	Precision ventilated refrigeration system	Number of Shelves	9 Shelves
Sections	3 Sections	Shipping Weight	500 pound
Type	Reach-In Freezer	Hinge Location	Left / Right
Installation Type	Freestanding	Interior Depth	23.2 inch
Interior Height	57.1 inch	Interior Material	Stainless Steel
Interior Width	68.1 inch	Material	Stainless Steel
Selling Unit	1/Each	Shelf Material	Epoxy Coated Steel Wire
Lighting	LED lighting	Refrigerant Class	Hydrocarbon
Refrigeration Type	Self-contained	Defrost Type	Auto Defrost



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Temperature Control	Electronic Control	Capacity	54 cubic feet
Shipping Width	75.4 inch	Shipping Depth	33.2 inch
Shipping Height	80.31 inch	Product Width	72 inch
Product Depth	31.5 inch	Product Height	77.9 inch
Product Weight	456 pound	Series	Platinum Frost Series

Platinum Frost Series 72" Commercial Reach In Freezer, 54 Cu.ft, 3 Door, Stainless Steel, -8°F to 0°F

Model: PFRF72



SALES & SUPPORT
(866) 446-7322

Chat on WhatsApp

CONNECT WITH US

