



Medal Equipment 81" Reach-In Refrigerator, 3 Doors, 72 cu. ft. Commercial, Stainless Steel, 2 Year Warranty

(Model: RFBM381)



★★★★★ (4.7/5)

Buy Now

WARRANTY

2 Year Warranty

SPECIAL FEATURES

- ✓ **Expansive Storage Capacity**
Generous 72 cu. ft. interior with four PE-coated wire shelves provides ample space for commercial kitchen storage needs.
- ✓ **Efficient Operation**
High-efficiency operation with R-290 hydrocarbon refrigerant and ECM fan system, backed by Energy Star certification.
- ✓ **Enhanced Visibility**
Interior LED lighting with shielded rocker switch control ensures clear product visibility in all conditions.
- ✓ **Comprehensive Warranty**
Backed by a 2-year warranty, providing reliable support from the manufacturer.
- ✓ **Simple Installation**
9 ft power cord with NEMA 5-15P plug enables easy setup on 115V single-phase connection.
- ✓ **Precise Temperature Control**
Dixell electronic thermostat maintains consistent 33°F-41°F range with digital LED display and automatic defrost for precise operation.
- ✓ **Reliable Construction**
Durable stainless steel interior and exterior with copper-coated condenser and evaporator ensure long-lasting commercial performance.
- ✓ **Mobile Operation**
Four 4" swivel casters with brakes provide stable mobility for flexible kitchen positioning.
- ✓ **Secure Cold Storage**
Three solid left/right-hinged swing doors with keyed locks protect inventory while magnetic gaskets seal in cold air.
- ✓ **Hassle-Free Access**
Vacuum release feature prevents pressure lock, ensuring doors open smoothly during busy service.



PRODUCT OVERVIEW

The Medal Equipment RFBM381 Reach-in Refrigerator is a high-performance cold storage solution designed for busy commercial kitchens. Built with a durable stainless steel interior and exterior in a sleek silver finish, it offers both strength and easy cleaning. With a generous 72 cu. ft. capacity, this 3-section unit has 4 PE-coated wire shelves (23.6" x 24.3") for ample storage for perishable goods. Interior LED lighting with shielded rocker switch control provides clear visibility.

Three solid swing left/right hinged doors with magnetic gaskets maintain a consistent temperature range between 33°F and 41°F, while the keyed door lock provides secure storage. The vacuum release air pressure relief feature makes frequent access smooth and hassle-free. Powered by a 1/2 HP bottom-mounted compressor, this reach-in refrigerator uses R-290 hydrocarbon refrigerant (5.29 oz capacity) and a forced-air cooling system with an efficient ECM fan.

It features a Dixell electronic thermostat, digital LED temperature display, and automatic defrost for precise, low-maintenance operation. The copper-coated condenser and copper evaporator ensure long-lasting performance. Measuring 81" W x 32.7" D x 82.3" H with casters, the freestanding unit is equipped with four 4" swivel casters with brakes for mobility and stability. A 9 ft power cord with a NEMA 5-15P plug ensures easy installation on a 115 V, 7.5 A, single-phase, 60 Hz connection.

The foamed-in-place polyurethane insulation provides temperature retention. Certified with cETLus, ETL Sanitation, and Energy Star for quality, hygiene, and efficiency, this refrigerator delivers 3200 BTU/hr cooling capacity. Backed by a 2-year warranty, it is an ideal choice for demanding hospitality environments.

CERTIFICATIONS



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	3 Doors	Access Type	Doors
Amps	7.5 ampere	Capacity	72 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors	Material	Stainless Steel
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	9 foot
Refrigerant Type	R-290	Sections	3 Sections
Shelf Material	PE Coated Wire Shelves	Temperature Range	33°F to 41°F
Type	Reach-In Refrigerator	Voltage	115 volt



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Hertz	60 hertz	Hinge Location	Left / Right
Horsepower	1/2 horsepower	Installation Type	Freestanding
Manufacturer	Medal Equipment	Country of Origin	China
Selling Unit	1/Each	Door Gasket	Magnetic Door Gasket
Lock Type	Keyed Door Lock	Number of Casters	4 Casters
Refrigeration Type	Forced Air	Caster Type	Swivel with brake
Interior Material	Stainless Steel	Temperature Control	Dixell Electronic Thermostat
Refrigerant Class	Hydrocarbon	Insulation Material	Foamed-in-Place Polyurethane
Caster Size	4 inch	Height with Casters	82.3 inch
Shelf Size	23.6 x 24.3 in	Product Weight	492 pound
Product Width	81 inch	Product Depth	33 inch
Product Height	82 inch	Shipping Depth	34.5 inch
Shipping Height	84.7 inch	Shipping Weight	571 pound
Shipping Width	83.7 inch	Refrigerant Capacity	5.29 oz
Condenser Coating	Copper	Evaporator	Copper
Lighting	LED, Shielded, Rocker Switch Control	Cooling Fans	ECM Fan
Defrost Type	Auto Defrost	Temperature Display	Digital LED Display
BTU/HR - Refrigerator	3200	Air Pressure Relief Door	Vacuum Release
Interior Depth	27.5 inch	Interior Height	59.4 inch
Interior Width	76.6 inch		