



ChillCore Series 73" Reach-in Commercial Refrigerator and Freezer Combo, 3 Section, Stainless Steel, 1 Year Warranty

(Model: CCRFC72)



★★★★★ (4.7/5)

Buy Now

WARRANTY

1 Year Warranty

SPECIAL FEATURES

- ✓ **Dual Temperature Control**
Separate refrigeration (33-41°F) and freezer (-8-0°F) compartments with independent digital temperature controls for precise climate management.
- ✓ **Professional Quality Construction**
Stainless steel construction with ETL, cETLus, and ETL Sanitation certifications ensures durability and food safety compliance.
- ✓ **Powerful Cooling System**
Dual top-mounted compressors (1/6 HP and 1/4 HP) with R-290 hydrocarbon refrigerant deliver efficient, reliable cooling performance.
- ✓ **Easy Installation**
Freestanding design with 5.9 ft power cord and standard NEMA 5-15P plug enables quick setup in any commercial space.
- ✓ **Commercial Grade Storage**
54 cubic foot capacity with nine PVC-coated shelves and three solid doors, perfect for high-volume commercial food storage needs.
- ✓ **Enhanced Mobility**
Five swivel casters, three with brakes, allow easy movement and secure positioning in commercial kitchen environments.
- ✓ **Energy Efficient Design**
LED interior lighting and modern R-290 refrigerant system maximize energy efficiency while maintaining optimal performance.
- ✓ **Simple Access**
Three solid doors with left/right hinges ensure convenient access to stored items across both temperature zones.



PRODUCT OVERVIEW

The CCRFC72 Dual Temperature Refrigerator/Freezer is a freestanding, commercial-grade stainless steel unit designed for high-capacity food storage and manufactured in China. Finished in silver, it features three solid doors, nine PVC-coated shelves, and a 54 cubic foot capacity for dual-zone cold storage.

The refrigeration compartment maintains a temperature range of 33°F to 41°F, powered by a 1/6 HP top-mounted compressor. The freezer section operates between -8°F to 0°F with a 1/4 HP top-mounted compressor. Both zones use a self-contained R-290 hydrocarbon refrigerant system and are regulated by a digital temperature control.

It runs on 115 V, 7 A, 60 Hz, 1 phase electrical service, and includes a 5.9 ft power cord with a NEMA 5-15P plug. The interior is illuminated by LED lighting. It includes five swivel casters, three with brakes for mobility. The unit's overall dimensions are 72.8 in W x 31.5 in D x 78 in H. Certified to ETL, cETLus, and ETL Sanitation standards, this includes a 1-year warranty.

null

CERTIFICATIONS

ETL Listed

ETL Sanitation Listed

DOE Certified

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Compressor Location	Top Mounted	Refrigerant Type	R-290
Shipping Weight	522 pound	Voltage	115 volt
Hertz	60 hertz	Number of Doors	3 Doors
Access Type	Doors	Amps	7 ampere
Capacity	54 cubic feet	Casters	With Casters
Door Type	Solid	Dutch Half Doors	Without Dutch Half Doors
Number of Shelves	9 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	5.9 foot
Shelf Material	Coated Wire Shelves	Type	Reach In Refrigerator & Freezer Combo
Hinge Location	Left / Right	Installation Type	Freestanding



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Temperature Range - Refrigerator	33°F to 41°F	Country of Origin	China
Material	Stainless Steel	Selling Unit	1/Each
Product Weight	437 pound	Caster Type	Swivel Casters, 3 with Brakes
Refrigerant Class	Hydrocarbon	Lighting	LED lighting
Shipping Width	76 inch	Shipping Depth	34 inch
Shipping Height	80 inch	Temperature Control	Digital
Temperature Range - Freezer	-8°F to 0°F	Sections	3 Sections
Product Width	72.8 inch	Product Depth	31.5 inch
Product Height	78 inch	Number of Casters	5 Casters
Series	ChillCore Series	Features	Efficient Air Cooling System
Defrost Type	Auto Defrost	Shelf Type	Adjustable
Door Style	Swing		

ChillCore Series 73" Reach-in Commercial Refrigerator and Freezer Combo, 3 Section, Stainless Steel, 1 Year Warranty

Model: CCRFC72



SALES & SUPPORT
(866) 446-7322

Chat on WhatsApp

CONNECT WITH US

