



PolarBox Series 8' x 10' Quick Ship Walk-In Cooler With Floor & Top Mounted Refrigeration

(Model: PBWF8X10-TM)



★★★★★ (4.7/5)

[Buy Now](#)

WARRANTY

10-Year Panel, 1-Year Door Parts, 2-Year Compressor & Parts, 1-Year Labor on Refrigeration Unit

SPECIAL FEATURES

- ✓ Durable Construction**
 24-gauge white galvanized steel panels with floor provide long-lasting strength and easy cleaning.
- ✓ Secure Access**
 Solid swing door with keyed lock, self-closing, and flush-mounted design protects contents and minimizes cold air loss.
- ✓ Reliable Cooling**
 Self-contained system with top-mounted condensing unit and evaporator using R-448A refrigerant delivers even, consistent cooling.
- ✓ Indoor/Outdoor Versatility**
 Suitable for flexible installation in indoor or outdoor commercial environments.
- ✓ Comprehensive Warranty**
 10-year panels, 1-year door parts, 2-year compressor & parts, and 1-year labor coverage protect your investment.
- ✓ Thermal Insulation**
 4-inch polyurethane panels (R-28) maintain stable internal temperatures efficiently.
- ✓ Easy Assembly**
 Modular cam-lock and tongue-and-groove panels with CFC and HFC-free materials enable fast, airtight setup.
- ✓ Commercial-Grade Power**
 Operates on 1-phase, 208/230 V, 60 Hz hardwired connection for dependable performance.
- ✓ Certified Compliance**
 UL Listed US, NSF Listed, and DOE certified for safety and efficiency.



PRODUCT OVERVIEW

PolarBox Series Walk-In Cooler is a commercial refrigeration unit ideal for restaurants, cafes, and food service operations. Constructed from 24-gauge white galvanized steel, it provides lasting structural integrity. Measuring 8 ft (W) x 10 ft (D) x 7 ft (H), it is suitable for indoor or outdoor use, with an floor that adds durability and simplifies cleaning for heavy-use storage areas.

It features 4-inch polyurethane insulation with R-28 thermal resistance, maintaining consistent interior temperatures. The solid swing door includes a keyed lock and self-closing flush-mounted design, reducing energy loss and keeping contents secure. Panels use modular cam-lock, tongue-and-groove design with CFC & HFC-free material, allowing easy assembly and tight alignment for optimal cooling efficiency.

The self-contained refrigeration system operates on R-448A refrigerant, with a top-mounted condensing unit and evaporator, using 1-phase 208/230 V power at 60 Hz. Certified UL Listed US, NSF Listed, and DOE, it provides compliant, reliable operation. Warranty coverage includes 10-year panels, 1-year door parts, 2-year compressor & parts, and 1-year labor on the refrigeration unit, offering complete commercial cold storage support.

CERTIFICATIONS

UL Listed US

NSF Listed

DOE

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Product Width	98 inch	Product Depth	118 inch
Product Height	87 inch	Door Height	77 inch
Nominal Depth	10 ft	Nominal Width	8 foot
Hertz	60 hertz	Phase	1 Phase
Voltage	208/230 volt	Door Type	Solid
Insulation Thickness	4 inch	Insulation Material	Polyurethane
Door Lock	Keyed Lock	Material	White Galvanized Steel
Type	Walk-In Cooler	Floor	With Floor
Plug Type	Hardwired	Refrigerant Type	R-448A
Usage	Indoor/Outdoor	Country of Origin	Proudly Made in America



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Selling Unit	1/Each	Door Style	Swing
Gauge	24 Gauge	Thermal Resistance	R-28
Features	Self-Closing, Flush-Mounted Door	Included	Condensing Unit and Evaporator
Number of Doors	1 Door	Nominal Height	7 foot
Compressor Location	Top Mounted	Hinge Type	Modular Cam-Lock, Tongue & Groove Design
Refrigeration Type	Top Mounted Refrigeration	Material Type	CFC & HFC Free
Series	PolarBox Series	Floor Material	Standard Galvanized Steel Floor