



Frigomax Series 54" Reach-In Refrigerator, Bottom Mounted, 2 Glass Door, Stainless Steel, 1 Year Warranty

(Model: FRRR54G)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Warranty

SPECIAL FEATURES

- Capacity**
A 46 cubic foot interior across two sections provides substantial refrigerated storage space for commercial kitchen operations.
- EC Fan Motor**
The EC fan motor supports consistent temperature distribution throughout the cabinet for reliable food handling conditions.
- ETL Certified**
This unit is both ETL Listed and ETL Sanitation Listed, meeting established safety and sanitation standards for commercial kitchen equipment.
- Tempered Glass Doors**
Double-layer tempered glass swing doors allow chefs to view stored contents at a glance without breaking the cold chain.
- Epoxy-Coated Shelves**
All 6 interior shelves carry an epoxy coating, offering resistance to moisture and corrosion typical in restaurant refrigeration use.
- Casters with Brakes**
Four casters with brakes allow the freestanding unit to be repositioned on the kitchen floor and locked firmly in place during service.



PRODUCT OVERVIEW

Frigomax Series reach-in refrigerator is a freestanding, two-section unit designed for commercial kitchen environments including restaurants, cafés, and food service operations requiring reliable cold storage at scale. With a 46 cubic foot capacity across two glass swing doors, this unit accommodates high-volume refrigeration needs while maintaining full visibility of stored contents without opening the doors.

The refrigerator holds a temperature range of 33°F to 41°F, controlled through an electronic temperature control system, making it suited for safe storage of perishable ingredients. Self-closing doors with a 90-degree stay-open feature support efficient workflow in busy kitchen settings, while the double-layer tempered glass doors add a measure of durability and insulation. The bottom-mounted 1/4 horsepower compressor draws 2.5 amperes at 115V, 60Hz, single-phase power through a NEMA 5-15P plug.

Interior organization is supported by 6 shelves finished with an epoxy coating, which offers resistance to moisture and corrosion common in food handling environments. The EC fan motor contributes to stable temperature distribution throughout the cabinet interior. Hinge placement on both left and right sides provides installation flexibility, and the unit arrives without Dutch half doors for a clean, full-panel door configuration.

Constructed from stainless steel in a silver finish, the unit measures 32 1/16" (L) x 54 1/8" (W) x 83 1/4" (H) and moves on 4 casters with brakes, allowing repositioning within the kitchen while remaining securely stationed during operation. Locks and keys are included for both doors. The unit is ETL Listed and ETL Sanitation Listed, meeting recognized standards for commercial food service equipment.

CERTIFICATIONS

ETL Listed

ETL Sanitation Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	2 Doors	Access Type	Door
Amps	2.5 ampere	Capacity	46 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Glass
Dutch Half Doors	Without Dutch Half Doors	Features	Self-Closing doors with 90 degree stay-open feature; EC fan motor; Door with 2 layers' tempered glass.
Material	Stainless Steel	Number of Shelves	6
Phase	1 Phase	Plug Type	NEMA 5-15P
Sections	2 Sections	Shelf Material	Epoxy coated
Temperature Range	33°F to 41°F	Type	Reach-In Refrigerator
Voltage	115 volt	Hertz	60 hertz



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Hinge Location	Left / Right	Horsepower	1/4 horsepower
Installation Type	Freestanding	Country of Origin	China
Selling Unit	1/Each	Shelf Coating Type	Epoxy
Lock Type	Keyed Door Lock	Number of Casters	4 Casters
Caster Type	Casters with brakes	Temperature Control	Electronic
Series	Frigomax Series	Product Width	54.13 inch
Product Depth	32.06 inch	Product Height	83.25 inch
Door Style	Swing		

Frigomax Series 54" Reach-In Refrigerator, Bottom Mounted, 2 Glass Door, Stainless Steel, 1 Year Warranty

Model: **FRRR54G**



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

