



Medal Equipment 54" Reach-In Refrigerator, 2 Doors, 49 cu. ft., Stainless Steel, Commercial, 2 Year Warranty

(Model: RFBM254)



★★★★★ (4.7/5)

Buy Now

WARRANTY
2 Year Warranty

SPECIAL FEATURES

- Large Storage Capacity**
 49 cu. ft. interior with PE-coated wire shelves accommodates high-volume storage while keeping items organized.
- Efficient Operation**
 R-290 hydrocarbon refrigerant, ECM cooling fans, and copper-coated condenser deliver efficient performance with reduced environmental impact.
- Durable and Hygienic Build**
 Stainless steel interior and exterior with silver finish resists corrosion, dents, and scratches, while enabling quick cleaning.
- Clear Interior Visibility**
 Shielded LED lighting with rocker switch illuminates contents for quick identification.
- Easy Mobility and Stability**
 Four 4-inch swivel casters with brakes allow effortless repositioning and stable placement.
- Consistent Cooling**
 1/4 HP bottom-mounted compressor with forced-air refrigeration maintains temperatures between 33°F and 41°F for safe food preservation.
- Strong Temperature Retention**
 Foamed-in-place polyurethane insulation and magnetic door gaskets minimize cold air loss for better efficiency.
- Secure and Easy Access**
 Two solid left/right-hinged swing doors with keyed locks protect inventory, while vacuum release ensures smooth opening.
- Low Maintenance Operation**
 Auto-defrost system reduces manual cleaning, ensuring uninterrupted kitchen workflow.



PRODUCT OVERVIEW

The Medal Equipment RFBM254 Reach-in Refrigerator delivers reliable cold storage for restaurants, hotels, and catering facilities. Built from a durable stainless steel interior and exterior, it offers exceptional corrosion resistance and a sleek silver finish that complements any commercial kitchen setup. With a spacious 49 cu. ft. capacity and PE-coated wire shelves (23.6" x 24.3"), it offers organized storage. It has two solid left/right hinged swing, keyed lock doors for easy access.

The vacuum release door feature prevents air pressure lock, while the magnetic door gasket ensures a tight seal. The foamed-in-place polyurethane insulation ensures temperature retention. Powered by a 1/4 HP bottom-mounted compressor, this unit operates with forced-air refrigeration to maintain a consistent 33°F to 41°F temperature range. The Dixell electronic thermostat and digital LED temperature display provide precise control, while the auto-defrost system reduces maintenance.

The copper-coated condenser, hydrocarbon R-290 refrigerant (3.7 oz capacity), and ECM cooling fans deliver efficient performance. Interior LED lighting with shielded rocker switch control ensures clear visibility. Measuring 53.9" W x 32.7" D x 82.3" H with 4" swivel casters (with brakes) for easy mobility, this refrigerator is designed for freestanding installation. Its copper evaporator, NEMA 5-15P plug, and 9 ft power cord add to the operational convenience.

Certified by cETLus, ETL Sanitation, and Energy Star, this refrigerator meets high safety and efficiency standards. It operates at 115 V/60 Hz/1-phase and is backed by a 2-year manufacturer warranty.

CERTIFICATIONS



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	2 Doors	Access Type	Doors
Amps	4.5 ampere	Capacity	49 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors	Material	Stainless Steel
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	9 foot
Refrigerant Type	R-290	Sections	2 Sections
Shelf Material	PE Coated Wire Shelves	Temperature Range	33°F to 41°F
Type	Reach-In Refrigerator	Voltage	115 volt



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Hertz	60 hertz	Hinge Location	Left / Right
Horsepower	1/4 horsepower	Installation Type	Freestanding
Manufacturer	Medal Equipment	Country of Origin	China
Selling Unit	1/Each	Door Gasket	Magnetic Door Gasket
Lock Type	Keyed Door Lock	Number of Casters	4 Casters
Refrigeration Type	Forced Air	Caster Type	Swivel with brake
Interior Material	Stainless Steel	Temperature Control	Dixell Electronic Thermostat
Refrigerant Class	Hydrocarbon	Insulation Material	Foamed-in-Place Polyurethane
Caster Size	4 inch	Height with Casters	82.3 inch
Shelf Size	23.6 x 24.3 in	Product Weight	428 pound
Product Width	54 inch	Product Depth	33 inch
Product Height	82 inch	Shipping Depth	34.5 inch
Shipping Height	84.7 inch	Shipping Weight	489 pound
Shipping Width	55.3 inch	Refrigerant Capacity	3.7 oz
Condenser Coating	Copper	Evaporator	Copper
Lighting	LED, Shielded, Rocker Switch Control	Cooling Fans	ECM Fan
Defrost Type	Auto Defrost	Temperature Display	Digital LED Display
BTU/HR - Refrigerator	2380	Air Pressure Relief Door	Vacuum Release
Interior Depth	27.5 inch	Interior Height	59.4 inch
Interior Width	49.2 inch		

Medal Equipment 54" Reach-In Refrigerator, 2 Doors, 49 cu. ft., Stainless Steel, Commercial, 2 Year Warranty

Model: RFBM254



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

