



ChefPro Series 36" Air Curtain with Variable Speed, Interior Mount, Aluminum

(Model: CPAC36)



★★★★★ (4.7/5)

[Buy Now](#)

WARRANTY

5 Year Limited Warranty

SPECIAL FEATURES

- ✓ **Interior Air Control**
Designed for interior mounting in commercial kitchen and foodservice openings.
- ✓ **Measured Air Output**
Rated at 1005 cfm with specified outlet and nozzle velocities for controlled air movement.
- ✓ **cULus Listed**
cULus listing supports compliance with commercial electrical standards.
- ✓ **Variable Speed Motor**
Two-speed motor operation supports adjustable airflow based on kitchen conditions.
- ✓ **Manual Operation**
Manual control type supports direct speed selection by kitchen staff.
- ✓ **Extended Warranty**
It includes a 5-year warranty by the manufacturer.



PRODUCT OVERVIEW

The ChefPro Series air curtain is designed for commercial kitchens and interior service openings where controlled air flow is required. Built from aluminized steel with a white and black finish, it suits restaurant and foodservice environments using interior mounting.

This 36" air curtain operates with electric power and uses a two-speed motor system rated at 1 x 1/5 HP. Manual controls allow selection between operating speeds based on kitchen airflow requirements.

The unit delivers an airflow rating of 1005 cfm, with an average outlet velocity of 1760 fpm and a maximum nozzle velocity of 3567 fpm. A 34.62" wide nozzle supports consistent air distribution across openings.

Overall dimensions measure 36" nominal width with a cabinet size of 13.5" (D) x 8.5" (H). It operates on 120 V, single-phase power at 60 Hz, is cULus listed, and includes a 5-year warranty by the manufacturer.

CERTIFICATIONS

UL Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Type	Air Curtain	Selling Unit	1/Each
Series	ChefPro Series	Country of Origin	Proudly Made in America
Material	Aluminized steel	Motor Type	Two Speed Motors
Horsepower	1/5 horsepower	Nozzle Size	34.62 in (W)
Air Flow	1005 (cfm)	Product Weight	41 pound
Product Depth	13.5 inch	Product Height	8.5 inch
Wattage	0.32 kilowatt	Installation Type	Wall & Top Mounting
Features	Average Outlet Velocity (fpm) 1760 , Maximum Nozzle Velocity 3567 (fpm)	Power Type	Electric
Phase	1 Phase	Hertz	60 hertz
Voltage	120 volt	Product Width	36 inch