

UCN-48R 48" Narrow Depth Undercounter Worktop Refrigerator



FEATURES

- Narrow 24" depth undercounter refrigerator
- Stainless steel exterior and interior
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with stay-open feature
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Hydro-Carbon R290 refrigerant
- 5" backsplash optional

The Coldline UCN 48" is a great refrigerator for an undercounter or worktop application. Interior and exterior made of stainless steel. Wheels, adjustable shelves, and self-closing doors come standard on all units. Eco-friendly R290 refrigeration system maintains 33 to 41 degree temperature to keep your food in the safe zone.

- cETLus Listed
 - ETL Sanitation Listed
- Certified to NSF Standard



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	48.4"W x 24"D x 38.2"H
Low Profile Dimensions	48.4"W x 24"D x 36.2"H
Interior Dimensions	47.7"W x 18.6"D x 29.1"H
Packaging Dimensions	50.4"W x 28.9"D x 40.7"H
Working Height	38.2"
Net Volume	7 cu. ft.
Unit Weight	165 lb.
Shipping Weight	196 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.3
Plug Type	NEMA 5-15P
Power Cord Length	96"

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	104°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 21"W x 10.82"D
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: UCN-48R

MFR ITEM #:



NEMA 5-15P

