



VALYR[™]
BY STRATA GPO

Project Name: _____
Location: _____
Item #: _____ Qty: _____
Model: _____

V1R23G / V2R49G Glass Door Reach-In Refrigerators

MODEL: ☐ V1R23G ☐ V2R49G

SPECIAL FEATURES

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (4 shelves; 88 lbs. weight capacity each)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor




V1R23G




V2R49G

TECHNICAL DATA

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMP. RANGE	ELECTRICAL	AMP DRAW	REFRIGERANT	DOORS / SHELVES	NET WEIGHT
V1R23G	27" x 35" x 81" (690 x 891 x 2056 mm)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	19 Cu Ft (542 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	1.9A	R600a	1 / 3	220 lbs (100 kg)
V2R49G	54" x 35" x 81" (1376 x 891 x 2056 mm)	49" x 27" x 60" (1252 x 735 x 1305 mm)	42 Cu Ft (1191 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	3.3A	R290	2 / 6	392 lbs (178 kg)



FRONT



FRONT



NEMA 5-15P



Intertek



Intertek

Available in export voltages and plug types.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

© 2026 VALYR