



ProKitchen Series 36" Dual Service Open Air Display Case Merchandiser, Black, 1 Year Warranty
(Model: PKACM36-3)



★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 1 Year
Compressor: 5 Year

SPECIAL FEATURES

- ✔ **Horizontal Display Layout**
Horizontal design with 2 adjustable stainless steel and glass shelves supports organized chilled merchandising in commercial kitchen environments.

✔ **Digital Temperature Control**
Digital thermostat maintains a temperature range of 30.2°F to 44.6°F for chilled storage conditions.

✔ **Certified Compliance Standards**
cETLus, ETL Sanitation, and NSF certifications align with commercial kitchen safety and sanitation requirements.
- ✔ **Curved Glass Access Design**
Lift-up top curved glass and rear refrigerated access support structured food display and handling in retail setups.

✔ **Insulated Cabinet Build**
CFC-free foamed-in-place polyurethane insulation supports internal temperature stability in commercial kitchen use.

✔ **Warranty Coverage**
It includes a 1-year warranty by the manufacturer and a 5-year compressor warranty for refrigeration components.



PRODUCT OVERVIEW

The ProKitchen Series Horizontal Air Curtain Merchandiser is designed for commercial kitchen and food retail environments such as supermarkets, cafés, and grab-and-go counters requiring horizontal chilled open display storage. It features an 11.8 cb3 capacity with a freestanding installation type supported by 4 casters for positioning flexibility in commercial kitchen layouts.

Constructed with black coated steel exterior and stainless steel interior, the unit measures 35.4" (W) x 33.2" (D) x 60.9" (H), supporting horizontal merchandising across 2 adjustable shelves made of stainless steel and glass. The shelf configuration supports organized chilled food display in commercial kitchen and retail environments with structured product presentation.

The system operates on 110 V, 60 Hz, single phase power with 12.5 A current draw and 1200 W wattage along with 0.5 HP compressor power. It uses R-290 refrigerant with a self-contained refrigeration system, supported by digital thermostat and digital temperature control. The temperature range is maintained between 30.2°F and 44.6°F for chilled display applications in food retail environments.

Unit features CFC-free foamed-in-place polyurethane insulation for thermal stability. It has ventilated air curtain operation with lift-up curved glass top and refrigerated rear access. LED illumination improves visibility, and a night curtain supports off-hour efficiency. Designed for ambient temperatures up to 75°F, it is cETLus, ETL Sanitation, NSF certified, and backed by a 1-year manufacturer warranty and 5-year compressor warranty.

CERTIFICATIONS

cETLus

ETL Sanitation

NSF

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Amps	12.5 ampere	Capacity	11.8 cubic feet
Casters	With Casters	Color	Black
Number of Shelves	2 Shelves	Phase	1 Phase
Plug Type	NEMA 5-20P	Power Cord Length	92 inch
Refrigerant Type	R-290	Temperature Range	30.2°F to 44.6°F
Type	Horizontal Air Curtain Merchandiser	Voltage	110 volt
Hertz	60 hertz	Horsepower	0.5 horsepower
Installation Type	Freestanding	Interior Material	Stainless Steel
Country of Origin	China	Material	Black Coated Steel
Selling Unit	1/Each	Product Weight	340 pound



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Product Width	35.4 inch	Product Depth	33.2 inch
Product Height	60.9 inch	Shipping Depth	36.2 inch
Shipping Height	66.7 inch	Shipping Weight	446 pound
Shipping Width	38.4 inch	Features	Night Curtain, LED Illumination, Lift Up Top Curved Glass, Refrigerated Rear Access Top
Series	ProKitchen Series	Style	Horizontal
Lighting	LED	Number of Casters	4 Casters
Temperature Control	Digital	Insulation	CFC Free Foamed In-Place Polyurethane
Defrost Type	Automatic	Cooling Type	Refrigerator
Shelf Type	Adjustable	Thermostat Type	Digital
Maximum Ambient Temperature	75 fahrenheit	Shelf Material	Stainless Steel And Glass
Wattage	1200 watt		

ProKitchen Series 36" Dual Service Open Air Display Case Merchandiser, Black, 1 Year Warranty

Model: PKACM36-3