



FrostLine Series 81" Reach-In Refrigerator, 3 Doors, 72 cu.ft., Stainless Steel, 1 Year Compressor Warranty

(Model: FLRR81)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Compressor

SPECIAL FEATURES

- Large Storage Capacity**
 72 cu. ft. space with four PE-coated wire shelves offers organized, ample storage for perishable items.
- Precise Temperature Management**
 Dixell electronic thermostat with digital LED display maintains steady 33°F to 41°F temperatures for optimal food safety.
- Secure Airtight Seal**
 Magnetic door gaskets provide a tight seal to lock in cold air and preserve freshness.
- Energy-Efficient Insulation**
 Foamed-in-place polyurethane insulation ensures superior cold retention and reduces energy consumption.
- Bright Interior Lighting**
 Shielded LED lights with rocker switch ensure clear visibility inside the refrigerator.
- Powerful and Efficient Cooling**
 1/2 HP bottom-mounted compressor with ECM fans delivers consistent forced-air refrigeration using eco-friendly R-290 refrigerant.
- Easy Access and Smooth Operation**
 Three solid swing doors with vacuum release air pressure relief prevent suction and allow hassle-free opening.
- Durable Thermal Components**
 Copper-coated condenser and evaporator improve heat transfer and enhance longevity.
- Low Maintenance**
 Automatic defrost function keeps the unit clean and running efficiently with minimal upkeep.



PRODUCT OVERVIEW

The FrostLine Series Reach-In Refrigerator is a high-capacity commercial refrigeration unit designed for commercial kitchens. Constructed with a durable stainless steel interior and exterior and finished in sleek silver, this refrigerator offers efficient cold storage across three solid swing-left/right hinged doors. Its spacious 72 cubic foot capacity can accommodate four PE-coated wire shelves (23.6" x 24.3"), allowing organized storage of perishable goods.

This unit is powered by a 1/2 HP bottom-mounted compressor using R-290 hydrocarbon refrigerant (5.29 oz capacity). It maintains a consistent temperature range of 33°F to 41°F, controlled precisely by a Dixell electronic thermostat and displayed on a digital LED screen. Additional features include auto defrost, shielded LED lighting with rocker switch control, and a vacuum release air pressure relief door that prevents door suction and enhances usability.

Operating on 115 V, 60 Hz power, it draws 7.5 amps through a 9-foot power cord with a NEMA 5-15P plug, ensuring reliable performance. Measuring 81" W x 32.7" D x 82.3" H with casters, this freestanding unit includes four 4-inch swivel casters with brakes for easy mobility and secure positioning. Its magnetic door gaskets provide an airtight seal, while the copper-coated condenser and evaporator improve heat transfer and durability.

The forced-air refrigeration and ECM fans provide efficient cooling. Foamed-in-place polyurethane insulation enhances thermal efficiency. Certified by cETLus, ETL Sanitation, and Energy Star, the Medal Equipment Reach-In Refrigerator comes with a one-year compressor warranty.

CERTIFICATIONS



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	3 Doors	Access Type	Doors
Amps	7.5 ampere	Capacity	72 cubic feet
Casters	With Casters	Color	Silver
Compressor Location	Bottom Mounted	Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors	Material	Stainless Steel
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	9 foot
Refrigerant Type	R-290	Sections	3 Sections
Shelf Material	PE Coated Wire Shelves	Temperature Range	33°F to 41°F
Type	Reach-In Refrigerator	Voltage	115 volt



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Hertz	60 hertz	Hinge Location	Left / Right
Horsepower	1/2 horsepower	Installation Type	Freestanding
Country of Origin	China	Selling Unit	1/Each
Door Gasket	Magnetic Door Gasket	Lock Type	Keyed Door Lock
Number of Casters	4 Casters	Refrigeration Type	Forced Air
Caster Type	Swivel with brake	Interior Material	Stainless Steel
Temperature Control	Dixell Electronic Thermostat	Refrigerant Class	Hydrocarbon
Insulation Material	Foamed-in-Place Polyurethane	Caster Size	4 inch
Height with Casters	82.3 inch	Shelf Size	23.6 x 24.3 in
Product Weight	492 pound	Product Width	81 inch
Product Depth	33 inch	Product Height	82 inch
Shipping Depth	34.5 inch	Shipping Height	84.7 inch
Shipping Weight	571 pound	Shipping Width	83.7 inch
Refrigerant Capacity	5.29 oz	Condenser Coating	Copper
Evaporator	Copper	Lighting	LED, Shielded, Rocker Switch Control
Cooling Fans	ECM Fan	Defrost Type	Auto Defrost
Temperature Display	Digital LED Display	BTU/HR - Refrigerator	3200
Air Pressure Relief Door	Vacuum Release	Interior Depth	27.5 inch
Interior Height	59.4 inch	Interior Width	76.6 inch
Series	FrostLine Series		

FrostLine Series 81" Reach-In Refrigerator, 3 Doors, 72 cu.ft., Stainless Steel, 1 Year Compressor Warranty

Model: FLRR81



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

