



ProKitchen Series 36" Gas Range with 2 Burners, 24" Griddle & Oven, Natural Gas - 131,000 BTU

(Model: PKCGR36-7)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Parts & Labor

SPECIAL FEATURES

- ✓ **Wide Griddle Surface**
24" smooth griddle supports flat-top cooking alongside burner operations in commercial kitchen use.

✓ **Cast Iron Build**
Cast iron burners and 12" x 12" grates support heavy cookware in restaurant cooking environments.

✓ **Mobility Design**
Freestanding unit with 4 casters (2 with brakes) supports flexible kitchen placement.
- ✓ **High Heat Output**
131,000 BTU total output with 30,000 BTU burners and 40,000 BTU griddle performance.

✓ **Oven Temperature Range**
Oven operates between 250°F and 550°F for baking and roasting applications.

✓ **Certified Equipment**
cETLus, ETL Sanitation, NSF certified with 1-year parts & labor warranty.



PRODUCT OVERVIEW

The ProKitchen Series Gas Range with Griddle & Oven is a freestanding commercial kitchen cooking unit designed for restaurants, hotels, and catering operations requiring combined burner, griddle, and oven functionality. The unit is constructed with a welded stainless steel frame suitable for commercial kitchen environments.

This gas range operates on natural gas with a total BTU output of 131,000 BTU. It includes 2 open lift-off burners, each rated at 30,000 BTU, built with cast iron burner construction and 12" x 12" cast iron grates. A 24" smooth griddle section is included with 40,000 BTU output for flat-top cooking applications in food service operations.

The integrated standard oven delivers 31,000 BTU with a U-shape burner system. It operates within a temperature range of 250°F to 550°F. The oven interior measures 26.6" (W) x 26" (D) x 13.9" (H) and includes 2 oven racks for baking and roasting workflows in commercial kitchen use.

The unit measures 36" W x 32.6" D x 60.3" H and weighs 403 lb. It features four casters, including two with brakes, stainless steel back riser and shelf, removable grates, and a pull-out crumb tray with angled handle. It includes a 3/4" NPT rear gas connection, standing stainless steel pilot, anti-clogging cover, thermal coupling safety valve, and stainless steel oven door. It is cETLus, ETL Sanitation, NSF certified, and includes a 1-year parts and labor warranty.

CERTIFICATIONS

cETLus Listed

ETL Sanitation Listed

Certified to NSF Standards

ETL US & Canada

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Burners	2 Burners	Burner BTU	30,000 BTU
Burner Style	Grates	Control Type	Manual
Features	Kick Plate Access, Stainless Steel Back Riser & Shelf, Removable Grates	Number Of Ovens	1 Oven
Oven BTU	31,000 BTU	Power Type	Gas
Total BTU	131,000 BTU	Type	Gas Range with Griddle & Oven
Installation Type	Freestanding	Oven Interior Width	26.6 in
Oven Interior Depth	26 in	Oven Interior Height	13.9 in
Griddle Width	24 inch	Griddle BTU	40,000 BTU
Country of Origin	China	Material	Stainless Steel
Color	Silver	Selling Unit	1/Each



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Gas Type	Natural Gas	Plate Type	Smooth
Number of Casters	4 Casters (2 with Brakes, 2 without Brakes)	Burner Type	Open Lift-Off Burners
Burner Shape	U-Shape Oven Burner	Oven Temperature Range	550°F
Product Weight	403 pound	Product Width	36 inch
Product Depth	32.6 inch	Product Height	60.3 inch
Shipping Depth	40 inch	Shipping Height	42 inch
Shipping Weight	507 pound	Shipping Width	41 inch
Series	ProKitchen Series	Burner Material	Cast Iron
Pilot Material	Standby Stainless Steel Pilot	Grate Material	Cast Iron
Tray Type	Pull Out Crumb Tray with Angled Handle Front	Grate Size	12" x 12"
Oven Racks	2 Oven Racks	Safety Features	Thermal Coupling Safety Valve
Oven Type	Standard Oven	Handle Material	Stainless Steel Handle for Bottom Oven
Pilot Protection	Anti-Clogging Pilot Cover	Gas Inlet Size Group	3/4" NPT Rear Gas Connection
Total Burner BTU	60,000 BTU	Total Oven BTU	31,000 BTU
Frame Type	Welded	Thermostat Temperature	250°F to 550°F
Door Material	Stainless Steel Oven Door		

ProKitchen Series 36" Gas Range with 2 Burners, 24" Griddle & Oven, Natural Gas - 131,000 BTU

Model: PKCGR36-7



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

