



PolarBox Series 6' x 6' Quick Ship Walk-In Freezer With Floor & Remote Refrigeration

(Model: PBFWF6X6-RM)



★★★★★ (4.7/5)

[Buy Now](#)

WARRANTY

10-Year Panel, 1-Year Door Parts, 2-Year Compressor & Parts, 1-Year Labor on Refrigeration Unit

SPECIAL FEATURES

- Stable Insulation**
 4-inch polyurethane panels with R-28 thermal resistance maintain consistent internal temperatures.
- Easy Assembly**
 Modular cam-lock panels with a tongue & groove design allow precise and straightforward installation.
- Eco-Friendly**
 CFC- and HFC-free insulation supports environmentally responsible refrigeration.
- Reliable Power**
 Hardwired single-phase system operating at 208/230 V, 60 Hz provides consistent electrical performance.
- Certified Safety**
 UL Listed (US), NSF Listed, and DOE certified for commercial compliance.
- Durable Build**
 24-gauge white galvanized steel panels with an floor provide a long-lasting, sturdy structure.
- Secure Access**
 Solid swing door with keyed lock, self-closing, flush-mounted design, heating wire, and pressure relief vent keeps stored items safe.
- Reliable Cooling System**
 The condensing unit and evaporator, equipped with thermostatic expansion and liquid line solenoid valves (TXV/TEV), regulate refrigerant flow efficiently.
- Flexible Installation**
 Designed for indoor or outdoor use without compromising cooling reliability.
- Warranty Protected**
 Includes 10-year coverage on panels, 1-year on door parts, 2 years on the compressor and parts, and 1 year of labor on the refrigeration unit.



PRODUCT OVERVIEW

The PolarBox Series Walk-In Freezer is designed for cafes and commercial kitchens, providing reliable cold storage for perishable goods. Made in America from 24-gauge white galvanized steel panels with an floor, this freezer measures 6 ft (W) × 6 ft (D) × 7 ft (H) and is suitable for both indoor and outdoor use.

The unit features a solid swing door with a keyed lock, self-closing, flush-mounted design, heating wire, and pressure relief vent. The door measures 77 in in height, providing convenient access. Panels connect via a modular cam-lock and tongue & groove hinge system for precise assembly.

4-inch polyurethane insulation with R-28 thermal resistance maintains stable internal temperatures, while the included condensing unit and evaporator, equipped with thermostatic expansion and liquid line solenoid valves (TXV/TEV), deliver efficient and reliable cooling. The system operates on a hardwired single-phase power supply at 208/230 V, 60 Hz.

This commercial walk-in freezer is UL Listed (US), NSF Listed, and DOE certified for commercial compliance. Warranty coverage includes 10 years on panels, 1 year on door parts, 2 years on the compressor and parts, and 1 year of labor on the refrigeration unit.

CERTIFICATIONS

UL Listed US

NSF Listed

DOE

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Product Width	79 inch	Product Depth	79 inch
Product Height	91 inch	Hertz	60 hertz
Phase	1 Phase	Voltage	208/230 volt
Door Type	Solid	Door Style	Swing
Insulation Thickness	4 inch	Insulation Material	Polyurethane
Door Lock	Keyed Lock	Material	White Galvanized Steel
Plug Type	Hardwired	Usage	Indoor/Outdoor
Type	Walk-In Freezer	Country of Origin	Proudly Made in America
Selling Unit	1/Each	Nominal Depth	6 ft
Nominal Width	6 foot	Door Height	77 inch



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Floor	With Floor	Included	Condensing Unit and Evaporator
Gauge	24 Gauge	Thermal Resistance	R-28
Features	Self-Closing, Flush-Mounted Door, Heating Wire and Pressure Relief Vent	Valve Type	Thermostatic Expansion, Liquid Line Solenoid Valve (TXV/TEV)
Number of Doors	1 Door	Nominal Height	7 foot
Hinge Type	Modular Cam-Lock, Tongue & Groove Design	Material Type	CFC & HFC Free
Series	PolarBox Series	Refrigeration Type	Remote Refrigeration
Floor Material	Standard Galvanized Steel Floor	Refrigerant Type	R-448A

PolarBox Series 6' x 6' Quick Ship Walk-In Freezer With Floor & Remote Refrigeration

Model: **PBFWF6X6-RM**



SALES & SUPPORT
(866) 446-7322


[Chat on WhatsApp](#)

CONNECT WITH US



