



ProKitchen Series 26" Reach-In Merchandiser Refrigerator, 1 Glass Swing Door, Black, 1 Year Warranty

(Model: PKCMR26)



★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 1 Year
Compressor: 5 Years

SPECIAL FEATURES

- Glass Door Display**
 The swing glass door and LED interior lighting support visibility of refrigerated products in foodservice environments.
- Adjustable Shelving**
 Four adjustable epoxy PVC coated steel shelves support organized storage and display.
- R-290 Refrigerant**
 The refrigeration system uses R-290 hydrocarbon refrigerant with a bottom-mounted 1/3 HP compressor.
- Digital Temperature Control**
 Electronic digital controls manage temperatures between 33°F and 41°F.
- Self-Closing Door**
 The door features self-closing operation with a 90-degree stay-open position for loading activities.
- Certified Construction**
 cETLus Listed, ETL Sanitation Listed, and UL & NSF Standards compliance are included.



PRODUCT OVERVIEW

The ProKitchen Series Reach-In Merchandiser Refrigerator is designed for restaurants, delis, bakeries, and cafés. It features a black coated steel exterior with an aluminum and stainless steel interior. The unit measures 25.6" (W) x 22.8" (D) x 79.4" (H) and provides a storage capacity of 13.3 cb3 for refrigerated food and beverage display.

This refrigerator features a single swing glass door with a right-side hinge location and pull-out door handle. The self-closing door includes a 90-degree stay-open feature for product loading and unloading. LED interior lighting and a white interior support product visibility in commercial kitchen and retail environments.

The ProKitchen Series refrigerator operates within a temperature range of 33°F to 41°F using electronic digital controls. It uses R-290 hydrocarbon refrigerant with a bottom-mounted 1/3 HP compressor. The unit operates on 115 V, 1 phase, 60 Hz power and draws 1.33 amps.

The refrigerator includes four adjustable epoxy PVC coated steel shelves, each with a load capacity of 90 lbs. Automatic defrost and foamed-in-place polyurethane insulation are integrated into the design. The unit is cETLus Listed, ETL Sanitation Listed, conforms to UL & NSF Standards, and includes a 1-year parts and labor warranty along with a 5-year compressor warranty.

CERTIFICATIONS

- cETLus Listed
- ETL Sanitation Listed
- Conforms to UL & NSF Standards

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Doors	1 Door	Access Type	Door
Amps	1.33 ampere	Capacity	13.3 cubic feet
Color	Black	Compressor Location	Bottom Mounted
Door Type	Glass	Features	Self-Closing Doors with 90 Degree Stay-Open Feature, Removable Installation Board
Number of Shelves	4 Shelves	Phase	1 Phase
Plug Type	NEMA 5-15P	Power Cord Length	84 inch
Refrigerant Type	R-290	Sections	1 Section
Temperature Range	33°F to 41°F	Type	Reach-In Merchandiser Refrigerator
Voltage	115 volt	Hertz	60 hertz
Hinge Location	Right	Horsepower	1/3 horsepower



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Interior Material	Aluminum and Stainless Steel	Country of Origin	China
Material	Coated Steel	Selling Unit	1/Each
Lighting	LED Interior Lighting	Shelf Material	Epoxy PVC Coated Steel
Insulation Material	Foamed-in-Place Polyurethane	Refrigerant Class	Hydro Carbon
Defrost Type	Automatic	Door Style	Swing
Maximum Ambient Temperature	90 fahrenheit	Series	ProKitchen Series
Product Weight	265 pound	Product Width	25.6 inch
Product Depth	22.8 inch	Product Height	79.4 inch
Shipping Depth	24.8 inch	Shipping Height	85 inch
Shipping Weight	297 pound	Shipping Width	27.5 inch
Temperature Control	Digital	Shelf Type	Adjustable
Control Type	Electronic	Interior Depth	19.8 inch
Interior Height	55 inch	Interior Width	22.9 inch
Shelf Width	22.3 in	Shelf Depth	16 in
Interior Color	White	Shelf Load Capacity	90 lbs
Handle	Pull Out Door Handle	Application	Restaurants, Delis, Bakeries, or Cafes

ProKitchen Series 26" Reach-In Merchandiser Refrigerator, 1 Glass Swing Door, Black, 1 Year Warranty

Model: PKCMR26



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

