



FumeGuard Series 5' Wall Mounted Grease Hood with Exhaust Fan, Stainless Steel - Heavy-Duty
(Model: FGWMGHF5)



★★★★★ (4.7/5)

Buy Now

WARRANTY
1 Year Warranty

SPECIAL FEATURES

- ✓ **Stainless Construction**
The hood features 18 Gauge 400 Series Stainless Steel construction for the specified heavy-duty commercial kitchen configuration.

✓ **Direct Drive Fan**
The exhaust assembly features a 13.5" Direct Drive Aluminum Up-Blast fan with 1/2 HP, 115 V, 1 Phase motor and variable speed controller.

✓ **UL Certification**
The grease hood is UL Listed to ANSI/UL710, as specified for the commercial kitchen hood.
- ✓ **Exhaust Airflow**
The exhaust system is rated at 1300 CFM, with the airflow specification provided for the wall-mounted grease hood.

✓ **Grease Filtration**
The hood uses stainless steel filters as the specified filter type for the grease hood assembly.

✓ **Warranty Included**
It includes a 1-year warranty by the manufacturer for the FumeGuard Series grease hood.



PRODUCT OVERVIEW

The FumeGuard Series Heavy-Duty Wall Mounted Grease Hood is designed for heavy-duty commercial kitchen applications requiring a wall-mounted grease hood with an exhaust fan. It measures 5 ft (L) x 4 ft (W) x 2 ft (H) and features 18 Gauge, 400 Series Stainless Steel construction in silver.

The hood includes a 13.5" Direct Drive Aluminum Up-Blast Exhaust Fan with UL762, 1/2 HP, 115 V, 1 Phase motor, and variable speed controller. The exhaust system provides a specified airflow of 1300 CFM and includes a 14" x 10" exhaust collar.

The included hood assembly features a built-in 3" rear standoff, right grease cup, and standard left and right cheeks. The filter configuration consists of stainless steel filters, while the hood provides the specified filtration type for the grease hood assembly.

Lighting is provided by 2 incandescent light fixtures with glass globes. The hood is classified as a Grease Hood, has a wall-mounted configuration, and is rated for Heavy Duty usage. It is UL Listed to ANSI/UL710 and includes a 1-year warranty by the manufacturer.

CERTIFICATIONS

UL Listed to ANSI/UL710

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Product Width	4	Product Height	2
Product length	5	Material Type	400 Series Stainless Steel
Air Flow	1300 CFM (Exhaust)	Exhaust Fan	13.5" Direct Drive Aluminum Up-Blast, UL762, 1/2 HP, 115 V, 1 Phase Motor with Variable Speed Controller
Filter Type	Stainless Steel Filters	Features	14" x 10" Exhaust Collar, Right Grease Cup, Standard Left and Right Cheeks
Selling Unit	1/Each	Country of Origin	China
Style	Heavy Duty Wall Mounted Hood	Type	Grease Hood Package
Mounting Configuration	Wall Mounted	Lighting	(2) Incandescent Light Fixture with Glass Globe
Series	FumeGuard Series	Gauge	18 Gauge
Material	Stainless Steel	Color	Silver
Included	Hood + Exhaust Fan + Built-in 3" Rear Standoff	Usage	Heavy Duty