



POT & PAN CHEMICAL SANITIZING CORNER DISHWASHER

S-C

Scullery
Low Temperature
Dishmachine




CMA MODEL: S-C




Temp-Sure
(Self contained 12kW heater)

Temp-Sure™ heater assures a continuous supply of 140° F hot water that guarantees excellent results.



Universal Slant Shelf
27"-42"



Sheet Pan Rack

FEATURES

- 40 racks / 160 covers per hour.
- All stainless steel construction assures long life and years of trouble free operation.
- Unique spray arm system features upper and lower stainless steel wash arms with reinforced end caps. Specially designed pull-pins allow wash arms to be easily removed for cleaning.
- Pump purging system improves results by eliminating soil and chemical carryover during rinse cycle.
- Top mounted controls include built-in chemical pumps and deliming system that assures proper chemical usage.
- Auto start/stop makes operation safe and easy.
- Large 27" high door opening accommodates larger items and utensils.
- Integrated scrap tray prevents food soil from entering drain system.
- Stainless steel impeller offers extended life and service.
- Built-in strainer in water inlet to prevent water valve from clogging.

AVAILABLE OPTIONS

- Solid/Powder Dual Bowl Dispenser
- Low Chemical Alarm
- Stainless Steel Dishtables
- Alternative Cycle Times
- Alternative Electrical Available for Export
- Stainless Steel Scrap Trap in lieu of Poly Pro

**CMA
MIZER®**
Registered Trademark




**S-C**

Chemical Sanitizing
Pot & Pan Single Rack
Dishwasher

WARNINGS:

- Electrical and Plumbing connections must be made by a qualified service company who will comply with all available Federal, State, and Local Health, Electrical, Plumbing and Safety codes.
- CMA recommends utilizing a water softening system to maintain water hardness measurements of 3.5 gpg (grains per gallon) or less. This will assure maximum results and optimum operation of the dishmachine.

**Specifications:**

MODEL S-C	USA	METRIC		USA	METRIC
OPERATING CAPACITY RACKS PER HOUR (NSF RATED)	40	40	WASH PUMP MOTORS HP	1	1
OPERATING CYCLE WASH TIME-SEC	45	45	DIMENSIONS		
RINSE TIME-SEC	30	30	DEPTH	25-3/4"	(65.4cm)
DWELL TIME-SEC	15	15	WIDTH (OUTSIDE DIMENSION)	25-3/4"	(65.4cm)
TOTAL CYCLE TIME	90	90	HEIGHT	66"-67"	(168-170cm)
WASH TANK CAPACITY	1.7 GAL.	(6.43 L)	STANDARD TABLE HEIGHT	34"	(86cm)
PUMP CAPACITY	68 GPM	(257 LPM)	MAXIMUM CLEARANCE FOR DISHES	27"	(68.5cm)
OPERATING TEMPERATURE REQUIRED	120°F	(49°C)	DRAIN CONNECTION (OFF FLOOR)	11-1/2"-12-1/2"	(29.2cm-31.7cm)
RECOMMENDED	140°F	(60°C)	STANDARD DISHRACK DIMENSIONS	1 20" x 20"	1 (50.8 X 50.8cm)
WATER CONSUMPTION PER RACK	1.7 GAL.	(6.43 L)	ELECTRICAL RATING	VOLTS	AMPS
PER HOUR	68 GPH	(257.4 LPH)		115	16
WATER REQUIREMENTS WATER INLET	3/4"	(1.9cm)	APPROXIMATE SHIPPING WEIGHT	299#	(135.6kg)
DRAIN-I.P.S.	2"	(5.1cm)	SHIPPING DIMENSIONS	PALLET & BOX @ 41" X 41" X 80"	

Summary Specifications: Model S-C

CMA Energy Mizer model S-C low temperature, chemical sanitizing commercial dishwasher meets NSF and UL sanitation and construction standards WITHOUT the use of BOOSTER or TANK HEATERS. The model S-C is constructed entirely of stainless steel. Each unit automatically washes, rinses and sanitizes food service utensils in standard 19-3/4" x 19-3/4" racks and accommodates oversized plates and utensils with a 27" high door clearance. Unit comes standard with upper and lower stainless steel wash arms. The model S-C incorporates a pump purging system that improves results by eliminating soil and chemical carryover during rinse cycle. **Note: This machine does not have built-in heaters, therefore produces no steam.**

Available Models: ■ S-AH Straight ■ S-C Corner ■ S-B

Advisory: CMA does NOT endorse "Tankless On-Demand" water heaters for use on CMA Dishmachine products. CMA DOES endorse, and highly recommends, the standard "tank" style water heaters, sized properly to handle each particular facility with their water heating requirements.



CMA MIZER
Registered Trademark

CMA Dishmachines 17707 Valley View Ave; Cerritos, CA 90703 • 800-854-6417 • 714-898-8781 • Fax: 714-895-2141 • www.cmadishmachines.com

CMA reserves the right to modify specifications or discontinue models without prior notification.

© 09-2024 CMA, Inc.

