



KitchenCore Series 60" Gas Range with 2 Ovens, 6 Open Burners, 24" Griddle, 306,000 BTU - Convertible

(Model: KWKGR6024)



★★★★★ (4.7/5)

Buy Now

WARRANTY

1 Year Parts & Labor

SPECIAL FEATURES

- ✓ **High Cooking Capacity**
6 hot plate burners, 2 griddle burners, and 2 ovens support high-volume cooking in commercial kitchen operations.
- ✓ **Gas Compatibility**
Supports natural gas and liquid propane with included regulator and specified nozzle sizes.
- ✓ **Mobility Setup**
Casters with 6" caster size support movement and placement in commercial kitchen layouts.
- ✓ **Oven Temperature Range**
Ovens operate between 175°F to 500°F with enamel coated interiors and chrome racks for food handling.
- ✓ **Griddle Cooking Surface**
24" griddle with polished steel plate and 3/4" thickness supports grilling tasks in restaurant kitchens.
- ✓ **Certified & Warranty**
CSA sanitation listed, NSF certified, and cCSAus listed, and it includes a 1-year parts & labor warranty by the manufacturer.



PRODUCT OVERVIEW

The KitchenCore Series Gas Range with Oven & Griddle is designed for chefs and restaurant operations handling high-volume cooking, grilling, and baking tasks in a commercial kitchen. It features stainless steel construction with a silver finish, supporting structured cooking environments. The unit includes 6 hot plate burners, a 24" griddle with 2 griddle burners, and 2 ovens, operating on gas power with natural gas and liquid propane compatibility.

This gas range delivers 30,000 BTU for hot plate burners, 28,000 BTU/hr for the griddle, and 35,000 BTU/hr oven output. It supports inlet gas pressure of 5" WC (NG) and 10" WC (LPG), with specified nozzle sizes for LPG and NG. A regulator is included, and the gas connection size is 3/4" NPT rear. The unit includes removable cast iron grates measuring 12" x 12".

The ovens operate within a temperature range of 175°F to 500°F and feature enamel coated interiors with 2 chrome racks and multiple position guides. The griddle includes a polished steel plate with 3/4" thickness and 24" width. Additional features include container fitment of 44, supporting structured kitchen operations.

It measures 60" (W) x 31.5" (D) x 56" (H) and is designed for freestanding installation. It includes casters with 6" caster size for movement. The unit is certified with CSA Sanitation, NSF, and cCSAus listings, supporting commercial kitchen standards. It includes a 1-year parts & labor warranty by the manufacturer.

CERTIFICATIONS

CSA Sanitation Listed

NSF Certified

cCSAus Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Number of Burners	6 Burners	Features	Container Fitment: 44, Removable Grates
Number Of Ovens	2 Ovens	Oven BTU	35,000 BTU/hr
Power Type	Gas	Type	Gas Range with Oven & Griddle
Gas Connection Size	3/4" NPT Rear	Installation Type	Freestanding
Top Configuration	Griddle	Griddle Width	24 inch
Griddle BTU	28,000 BTU/hr	Country of Origin	China
Material	Stainless Steel	Color	Silver
Selling Unit	1/Each	Gas Type	Natural Gas / Liquid Propane
Number of Griddle Burners	2 Griddle Burners	Inlet Gas Pressure	5" WC (NG) / 10" WC (LPG)
Hot Plate BTU	30,000 BTU	Number of Hot Plate Burners	6 Hot Plate Burners



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Casters	With Casters	Nozzle Size	LPG: 52 (Griddle), 43 (Oven) / NG: 40 (Oven)
Oven Interior Material	Enamel Coated	Oven Temperature Range	175°F to 500°F
Product Weight	626.12 pound	Product Width	60 inch
Product Depth	31.5 inch	Product Height	56 inch
Shipping Depth	36.8 inch	Shipping Height	38.2 inch
Shipping Weight	744.92 pound	Shipping Width	62 inch
Series	KitchenCore Series	Included	Regulator Included
Caster Size	6 inch	Grate Material	Cast Iron
Grate Size	12" x 12"	Rack Positions	Multiple Position Guides
Oven Racks	2 Chrome Racks	Griddle Plate Size	3/4" Thickness
Griddle Plate Material	Polished Steel	Burner Configuration	Hot Plates + Griddle + Oven

KitchenCore Series 60" Gas Range with 2 Ovens, 6 Open Burners, 24" Griddle, 306,000 BTU - Convertible

Model: KWKGR6024



SALES & SUPPORT
(866) 446-7322

 Chat on WhatsApp

CONNECT WITH US

