



VALYRTM
BY STRATA GPO

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

V1R23 / V2R49 / V3R72 Solid Door Reach-In Value Refrigerators

MODEL: ☐ V1R23 ☐ V2R49 ☐ V3R72

SPECIAL FEATURES

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (4 shelves; 88 lbs. weight capacity each)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



V1R23




V2R49




V3R72

TECHNICAL DATA


MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMP. RANGE	ELECTRICAL	AMP DRAW	REFRIGERANT	DOORS / SHELVES	NET WEIGHT
V1R23	27" x 34" x 81" (690 x 864 x 2056 mm)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	23 Cu Ft (542 L)	33°F to 41°F (1°C to 5°C)	115V / 60Hz / 1PH	3.1A	R290	1 / 3	205 lbs (93 kg)
V2R49	54" x 34" x 81" (1376 x 864 x 2056 mm)	49 1/4" x 29" x 51 3/8" (1252 x 735 x 1305 mm)	42 Cu Ft (1191 L)	33°F to 41°F (1°C to 5°C)	115V / 60Hz / 1PH	7.2A	R290	2 / 6	348 lbs (158 kg)
V3R72	81" x 34" x 81" (2062 x 864 x 2056 mm)	76 1/4" x 29" x 51 3/8" (1938 x 735 x 1305 mm)	65 Cu Ft (1841 L)	33°F to 41°F (1°C to 5°C)	115V / 60Hz / 1PH	7.9A	R290	3 / 9	454 lbs (206 kg)



FRONT



FRONT



FRONT



NEMA 5-15P



Intertek



Intertek

Available in export voltages and plug types.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.