



Platinum Frost Series 48" Commercial Undercounter Refrigerator, 12 Cu.ft, 2 Door, Stainless Steel, 33°F to 41°F, 115v

(Model: PFUR48)

★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 2 Years
Compressor: 6 Years



SPECIAL FEATURES

- ✔ **Space-Efficient Storage**
Compact 12 cubic foot capacity with two sections and shelves, perfect for small restaurants, cafés, and prep stations requiring efficient refrigerated storage.

✔ **Commercial-Grade Construction**
Durable stainless steel interior and exterior construction with silver finish, designed for heavy commercial use and easy cleaning.

✔ **Enhanced Mobility**
Four built-in casters enable easy movement and repositioning, perfect for dynamic commercial kitchen environments.

✔ **Safety Certified**
ETL Listed, ETL Sanitation certified, and cETLus approved, meeting all necessary safety and sanitation standards.

✔ **Simple Power Requirements**
Operates on standard 115V power with NEMA 5-15P plug and 7.8 ft cord, drawing only 1.5 amps and 195 watts.
- ✔ **Professional Temperature Control**
Maintains precise temperature range of 33°F to 41°F with auto defrost functionality and reliable R-290 refrigerant system.

✔ **Flexible Door Access**
Two solid swing doors with adjustable left/right hinge placement maximize accessibility and adapt to different space configurations.

✔ **Comprehensive Warranty**
Backed by 2-year parts and labor warranty plus extended 6-year compressor coverage for long-term reliability.

✔ **Efficient Cooling System**
Rear-mounted, front/rear breathing compressor ensures optimal airflow and cooling performance in tight spaces.



PRODUCT OVERVIEW

This undercounter refrigerator is ideal for small restaurants, cafés, or prep stations that need compact, efficient refrigerated storage. Made of stainless steel with a silver finish, it offers a 12 cubic foot capacity and includes two solid swing doors with left/right hinge placement, two sections, and two shelves. The interior dimensions measure 43.7" x 19.9" x 24.8" (W x D x H), built with stainless steel for durability and easy cleaning.

It uses a rear-mounted, front/rear breathing compressor and a self-contained R-290 refrigerant system. The unit maintains a temperature range of 33°F to 41°F, includes auto defrost, and runs on 115V, 60 Hz, single-phase power. It draws 1.5 amps, uses 195 watts, and connects via a NEMA 5-15P plug with a 7.8 ft power cord. The refrigerator stands on four casters for mobility and is designed for freestanding undercounter installation.

Product dimensions are 48" x 29.9" x 35.2" (W x D x H), this unit is ETL Listed, ETL Sanitation certified, and cETLus approved. It is sold as 1 each and comes with a 2-year parts and labor warranty and a 6-year compressor warranty.

CERTIFICATIONS

- ETL Listed
- ETL Sanitation Listed

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Power Cord Length	7.8 foot	Amps	1.5 ampere
Voltage	115 volt	Refrigerant Type	R-290
Temperature Range	33°F to 41°F	Hertz	60 hertz
Phase	1 Phase	Number of Doors	2 Doors
Access Type	Door	Capacity	12 cubic feet
Casters	With Casters	Color	Silver
Door Type	Solid	Number of Shelves	2 Shelves
Plug Type	NEMA 5-15P	Sections	2 Sections
Shipping Weight	243 pound	Type	Undercounter Refrigerator
Hinge Location	Left / Right	Interior Depth	19.9 inch
Interior Height	24.8 inch	Interior Width	43.7 inch
Country of Origin	China	Material	Stainless Steel
Selling Unit	1/Each	Product Weight	220 pound
Installation Type	Undercounter	Number of Casters	4 Casters
Compressor Location	Rear Mounted	Defrost Type	Auto Defrost
Wattage	195 watt	Shipping Width	50.2 inch



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Shipping Depth	31.1 inch	Shipping Height	38.4 inch
Compressor Style	Front / Rear Breathing	Product Width	48 inch
Product Depth	29.9 inch	Product Height	35.2 inch
Series	Platinum Frost Series		

Platinum Frost Series 48" Commercial Undercounter Refrigerator, 12 Cu.ft, 2 Door, Stainless Steel, 33°F to 41°F, 115v

Model: PFUR48