



Platinum Frost Series 28" Commercial Undercounter Freezer, 6.3 Cu.ft, Single Door, Stainless Steel, -8°F to 0°F, 115v

(Model: PFUF28)



★★★★★ (4.7/5)

Buy Now

WARRANTY

Parts & Labor: 2 Years
Compressor: 6 Years

SPECIAL FEATURES

- Space-Saving Design**
Compact undercounter freezer with 6.3 cubic feet capacity, perfect for small kitchens and tight spaces while maximizing storage efficiency.
- Temperature Control**
Electronic temperature control system maintains consistent temperatures between -8°F to 0°F with auto defrost functionality.
- Enhanced Security**
Features a locking door mechanism to secure contents, ideal for commercial environments requiring controlled access.
- Comprehensive Warranty**
Includes 2-year parts and labor warranty plus extended 6-year compressor warranty for long-term protection.
- Flexible Installation**
Freestanding design with 8.2 ft power cord and NEMA 5-15P plug allows for versatile placement options.
- Professional Grade Construction**
Durable stainless steel interior and exterior with silver finish, featuring one solid swing door and epoxy-coated steel wire shelf.
- Energy Efficient**
Self-contained refrigeration system uses R-290 hydrocarbon refrigerant, operating at 115V/60Hz with only 2.4 amps and 250 watts consumption.
- Easy Mobility**
Mounted on casters for convenient movement and repositioning, perfect for dynamic kitchen environments.
- Safety Certified**
ETL Listed, ETL Sanitation Listed, and OE certified, ensuring compliance with industry safety and sanitation standards.



PRODUCT OVERVIEW

This compact undercounter freezer is ideal for small kitchens, cafés, or backup cold storage areas where space is tight but reliability matters. Made from stainless steel with a silver finish, it offers 6.3 cubic feet of storage capacity and includes one solid swing door (right-hinged), one epoxy-coated steel wire shelf, and a stainless steel interior measuring 23.8" x 19.9" x 24.8" (W x D x H).

It uses a self-contained refrigeration system with R-290 hydrocarbon refrigerant and includes auto defrost and electronic temperature control, maintaining temperatures between -8°F to 0°F. The unit operates on 115V, 60 Hz, single-phase power, drawing 2.4 amps and 250 watts, and connects using a NEMA 5-15P plug with an 8.2 ft power cord.

Built for freestanding installation, it also features a locking door, durable copper coil, and sits on casters for easy mobility.

The freezer's dimensions are 27" x 29.9" x 35.2" (W x D x H), this unit is ETL Listed, ETL Sanitation Listed, and OE certified. It's sold as 1 each and includes a 2-year parts and labor warranty along with a 6-year compressor warranty.

CERTIFICATIONS

ETL Listed

ETL Sanitation Listed

OE certified

SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Power Cord Length	8.2 foot	Amps	2.4 ampere
Voltage	115 volt	Refrigerant Type	R-290
Temperature Range	-8°F to 0°F	Hertz	60 hertz
Phase	1 Phase	Number of Doors	1 Door
Access Type	Door	Capacity	6.3 cubic feet
Casters	With Casters	Color	Silver
Door Type	Solid	Features	Locking Door, Durable Copper Coil
Number of Shelves	1 Shelf	Plug Type	NEMA 5-15P
Sections	1 Section	Shipping Weight	179 pound
Type	Undercounter Freezer	Hinge Location	Right
Interior Depth	19.9 inch	Interior Height	24.8 inch
Interior Width	23.8 inch	Material	Stainless Steel
Selling Unit	1/Each	Product Weight	168 pound
Temperature Control	Electronic Control	Interior Material	Stainless Steel
Shelf Material	Epoxy Coated Steel Wire	Door Gasket	Magnetic Door Gasket
Drawer Gasket	Magnetic Door Gasket	Refrigerant Class	Hydrocarbon



SPECIFICATION

ATTRIBUTE	VALUE	ATTRIBUTE	VALUE
Refrigeration Type	Self-contained	Installation Type	Freestanding
Defrost Type	Auto Defrost	Shipping Width	30.3 inch
Shipping Depth	31.1 inch	Shipping Height	38.4 inch
Wattage	250 watt	Product Width	27 inch
Product Depth	29.9 inch	Product Height	35.2 inch
Series	Platinum Frost Series		

Platinum Frost Series 28" Commercial Undercounter Freezer, 6.3 Cu.ft, Single Door, Stainless Steel, -8°F to 0°F, 115v

Model: PFUF28



SALES & SUPPORT
(866) 446-7322

